SRY	Driver:		Event:			
	Date:		Track:			
Setup Sheet	Qualify:	TQ: Main:	: Finish: _	Best Lap 1	'ime:	
Ride Height:	Bum	p Steer Spacing:			•66	
Camber:	_ /					
Toe:				Dell Cond Constant		
Ride Height: Camber: Toe: Anti-Roll Bar:				Ball Stud Spacing:	/	
Wheelbase Shim:		7			300	
Wheel Hex:					3 2	
Caster Block:			Ball Stud:		2 1 9	
Arm Stiffener: Yes No [ī		Ball Stud S	pacina:	00	
	FF Suspension Holder Alu Brass	1°			30	
	Alu Diuss_				28 FO	
				J		
	FR Suspension Holder	<u>(655</u>)			O h	
	Alu Brass	1° □ 0.5° □				
				BA		
Ride Height: Camber: Anti-Roll Bar: Wheel Hex:	Rear Chassis Stiffener S	Screws → Front		(90	
Camber:	_			`	30	
Anti-Roll Bar:	_ 0 0 0				21	
	_				0	
Hub Spacing: Forward Middle Back						
Arm Spacing: Forward Back		1° 0.5°			30	
Arm Stiffener: Yes No	- 1000)	38	
Chassis Stiffener: Std Carbon [````				
	RR Suspension Holder					
	Alu Brass	1°				
				00	UO	
				BA		
Radio: Servo: EPA: Throttle: % Brake: % ESC: ESC Settings: Motor: Timing: # of Pads: Pinion: Spur: Battery: Pattern Pacition:		vid:	Shocks:	Front Rea	ır O	
EPA: Throttle: % Brake: % Center		Fluid:	Piston:			
ESC: Rear Diff		id: Fluid: Spring:				
ESC Settings: Slippe		ch:	Limiters:			
Motor: Timing:	# of Pads:		Stroke:			
Pinion: Spur:			Eyelet Length:		Stroke	
Battery:			Notes:			
Battery Position:		<u> </u>				
c coul	D Estantana D	1				
A	rge Extra Large	Front Tires:		Body:		
	troturf Multi Surface	Front Compound:		Wing:		
Traction: Low Medium High		Front Insert:		Total Vehicle Weight:		
Traction: Low Medium High Moisture: Dry Damp We Condition: Indoor Outdoor Du Bumpy Grooved Sm		Rear Tires:		Chassis Weights:		
Condition: Indoor Dutdoor Dusty Hard Packed Bumpy Grooved Smooth Loamy		-	Rear Compound:			
	Rear Insert:					
Temperature: Ambient:	Wheel (F/R):	Wheel (F/R):				
LUOLES	<u>LYOU'GS</u>	<u>Notes</u>				
Comments						
Ě						
<u>e</u>						
					 	

Team Corally