



## MODIFIED SETUP

Driver: Jörn Neumann

| Track/Event: 2014 European Championship Trelleborg/S  Date: 2014 July 27 |                                  |   |   |                    |   |   |                                     |  |           |               |  |
|--|----------------------------------|---|---|--------------------|---|---|-------------------------------------|--|-----------|---------------|--|
|  |                                  |   |   |                    |   |   |                                     |  |           |               |  |
| Car: Durango   |                                  |   |   |                    | ESC Firmware: V3.0_111208_MOD Traction: |   |                                     |  |           |               |  |
| Motor: VST2 550 7.5T   |                                  |   |   |                    | Battery: - Medium High                  |   |                                     |  |           | •             |  |
| Rotor: Std   |                                  |   |   |                    | Comments/Results:                       |   |                                     |  |           |               |  |
| T  | iming: Std                       | Gear  | Gearing: 22/87  2014 European Champion 4wd Modified Buggy |                    |   |   |                                     |  |           |               |  |
| S  | ettings                          | 1   | 2   | 3                  | 4                                       | 5   | 6                                   | 7  | 8         | 9             |  |
| 1  | Running Mode                     | X<br>Forward,<br>Brake  | Forward,<br>Reverse with<br>Brake                         | Foward,<br>Reverse | Blinky Mode*<br>Forward,<br>Brake       | Blinky Mode*<br>Forward,<br>Reverse with<br>Brake | Blinky Mode*<br>Forward,<br>Reverse | * In the blinky mode the settings 10-15 are not available and deactivated. |           |               |  |
| 2  | Drag Brake Force                 | 0%  | 5%  | 10%                | 15%                                     | 20%   | 25%                                 | 30%  | 100%      | User Setting: |  |
| 3  | Low Voltage<br>Cut-Off Threshold | No Protection   | 2.6V/Cell   | 2.8V/Cell          | X<br>3.0V/Cell                          | 3.2V/Cell   | 3.4V/Cell                           | User Setting:  |           |               |  |
| 4  | Start Mode(Punch)                | Level 1   | Level 2   | Level 3            | X<br>Level 4                            | Level 5   | Level 6                             | Level 7  | Level 8   | Level 9       |  |
| 5  | Max Brake Force                  | 12.50%  | 25%   | 37.50%             | 50%                                     | 62.50%  | 75%                                 | 87.50%   | X<br>100% |               |  |
| 6  | Max Reverse Force                | X<br>25%  | 50%   | 75%                | 100%                                    |   |                                     |  |           |               |  |
| 7  | Initial Brake Force              | X<br>Drag Brake   | 0%  | 20%                | 40%                                     |   |                                     |  |           |               |  |
| 8  | Neutral Range                    | X<br>6% (Narrow)  | 9% (Normal)   | 12% (Wide)         |   |   |                                     |  |           |               |  |
| 9  | Over-heat Protection             | Enable  | Disable   |                    |   |   |                                     |  |           |               |  |
| 10   | BoostTiming**                    | 0°  | User Setting:   |                    |   |   | (0°-16°   1° steps)                 |  |           |               |  |
| 13   | Turbo Timing                     | 10°   | User Setting:   |                    |   |   | (0°-20°   1° steps)                 |  |           |               |  |
| 14   | Turbo Slope Rate                 | 3°/0.1s   | 6°/0.1s   | 12°/0.1s           | 18°/0.1s                                | 24°/0.1s  | Fastest                             |  |           |               |  |
| 15   | Turbo Delay                      | X<br>0s/off   | 0.1s  | 0.2s               | 0.3s                                    | 0.4s  | 0.5s                                | 0.6s   | 0.7s      | 0.8s          |  |
|  |                                  |   |   |                    |   |   |                                     |  |           |               |  |
|  | **Boost Timing is no             | **Boost Timing is not available for speed controllers with 0° timing software |   |                    |   |   |                                     |  |           |               |  |