

Name of Driver		Date		Track		Engine		Plug		Muffler	
				Condition: _____		Temp: _____					
Spur Gear	Clutch Bell	Clutch Spring		Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel		
T	<input type="checkbox"/> Std. <input type="checkbox"/> LW	<input type="checkbox"/> 0.90 <input type="checkbox"/> 1.00 <input type="checkbox"/> 0.95 <input type="checkbox"/> 1.10		Carbon <input checked="" type="checkbox"/> Aluminum <input checked="" type="checkbox"/>	Tire: _____ Compounds: _____						

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	<input type="checkbox"/> 10/20 <input type="checkbox"/> 12/18 <input type="checkbox"/> LSD Ring Gear <input type="checkbox"/> 43/13 <input type="checkbox"/> 42/12 #	<input type="checkbox"/> 10/20 <input type="checkbox"/> 12/18 <input type="checkbox"/> LSD Diff. Size <input type="checkbox"/> Small <input type="checkbox"/> Large #	<input type="checkbox"/> 10/20 <input type="checkbox"/> 12/18 <input type="checkbox"/> LSD Ring Gear <input type="checkbox"/> 43/13 <input type="checkbox"/> 42/12 #

● Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration	Size - type
Shock Piston	B : Black W : White T : Taper	φ x
Shock Oil	#	#
Shock Spring		

● Ride Height

Front	Rear
mm	mm

● Rebound

Front	Rear
mm	mm

● Camber Angle

Front	Rear
+ ° - °	+ ° - °

● Toe Angle

Front	Rear
+ ° - °	<input type="checkbox"/> 2.5° <input type="checkbox"/> 3° <input type="checkbox"/> 3.5°

● Wheelbase

Collar of Rear Hub	Front Side _____ mm Rear Side _____ mm
--------------------	---

● Shock Mount Position

<Front> <Rear>

Sus. Arm

Front	<input type="checkbox"/> In <input type="checkbox"/> Out
Rear	<input type="checkbox"/> In <input type="checkbox"/> Out

● Rear Upper Arm Position

Plastic
 Aluminum

Hub Carrier Bush
 Plastic
 Brass

<input type="checkbox"/> Narrow <input type="checkbox"/> Std. <input type="checkbox"/> Wide


● Front Sus. Arm

<input type="checkbox"/> SS <input type="checkbox"/> Soft (Std.) <input type="checkbox"/> Hard
--

● Front Sus. Bush

Rear Side	
-----------	--

● Front Upper Arm Position




● Front Wheel Hub

<input type="checkbox"/> Narrow <input type="checkbox"/> Std. <input type="checkbox"/> Wide

● Front Hub Carrier

<input type="checkbox"/> Plastic <input type="checkbox"/> Aluminum
<input type="checkbox"/> 13° <input type="checkbox"/> 16° <input type="checkbox"/> 17.5° <input type="checkbox"/> 19° <input type="checkbox"/> 22°



● Lower Bush

<input type="checkbox"/> Plastic <input type="checkbox"/> Brass
-1° 0° +1°

● Rear Sus. Bush

Front Side	
Rear Side	


● Rear Sus. Arm

<input type="checkbox"/> Soft (Std.) <input type="checkbox"/> Hard
Rear Sus. Bush
Short
Medium
Long

● Servo Horn

Steering	Throttle
<input type="checkbox"/> Plastic <input type="checkbox"/> AL. Long <input type="checkbox"/> AL. Short	<input type="checkbox"/> Plastic <input type="checkbox"/> AL.

● Steering Plate



● Sway Bar

Front	Rear
φ	φ
mm	mm

● Weight

Front	Rear
<input type="checkbox"/> None <input type="checkbox"/> IFW604-10 <input type="checkbox"/> IFW604-20 <input type="checkbox"/> other	<input type="checkbox"/> None <input type="checkbox"/> IFW605-10 <input type="checkbox"/> IFW605-20 <input type="checkbox"/> other

● Wing

<input type="checkbox"/> IF491(TK14) Flap <input type="checkbox"/> None <input type="checkbox"/> 5mm <input type="checkbox"/> 8mm <input type="checkbox"/> Holes

Am0 - PetitRC

NOTES