

InfernoMP10 SET UP SHEET

ver.1.03



Name of Driver		Date		Track		Engine		Plug		Muffler	
Renaud Savoya		13/02/22		MBM Montpellier		Picco P3TT		P5TH		EFRA 2166	
		Condition		Dried wet		Temperature: 13°C					
Spur Gear	Clutch Bell	Clutch Spring		Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel		
45 T	<input type="checkbox"/> Std. <input checked="" type="checkbox"/> LW 13 T	<input type="checkbox"/> 0.90 <input type="checkbox"/> 1.00 <input checked="" type="checkbox"/> 0.95 <input type="checkbox"/> 1.10	Carbon <input checked="" type="checkbox"/> 3 Aluminum <input type="checkbox"/>	Tire : AKA P1 Compounds: CI	AKA	Kyosho soft	TKI2	Hot Road GT			

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	<input checked="" type="checkbox"/> 10/20 <input type="checkbox"/> 12/18 <input type="checkbox"/> LSD	<input checked="" type="checkbox"/> 10/20 <input type="checkbox"/> 12/18 <input type="checkbox"/> LSD	<input checked="" type="checkbox"/> 10/20 <input type="checkbox"/> 12/18 <input type="checkbox"/> LSD
Ring Gear	<input checked="" type="checkbox"/> 43/13 <input type="checkbox"/> 42/12	Diff. Size <input checked="" type="checkbox"/> Small <input type="checkbox"/> Large	<input checked="" type="checkbox"/> 43/13 <input type="checkbox"/> 42/12
	# 5k	# 7k	# 3k

● Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration	Size type
Shock Piston	B : Black W : White T : Taper	Size type
Shock Oil	# 300	# 450
Shock Spring	IFS001-7515	IFS002-915

● Ride Height

Front	Rear
25 mm	28 mm

● Rebound

Front	Rear
107 mm	124 mm

● Camber Angle

Front	Rear
+ 2 °	+ 2 °


● Toe Angle

Front	Rear
+ 2 °	<input type="checkbox"/> 2.5° <input checked="" type="checkbox"/> 3° <input type="checkbox"/> 3.5°

● Wheelbase

Collar of Rear Hub	Front Side 5 mm Rear Side 0 mm
--------------------	-----------------------------------

● Shock Mount Position



Sus. Arm	Front <input type="checkbox"/> In <input type="checkbox"/> Out Rear <input type="checkbox"/> In <input checked="" type="checkbox"/> Out
----------	--


Shock Stay

Front	<input type="checkbox"/> Short <input checked="" type="checkbox"/> Long <input type="checkbox"/> Alu <input checked="" type="checkbox"/> Carbon
Rear	<input type="checkbox"/> Short <input checked="" type="checkbox"/> Long <input type="checkbox"/> Alu <input checked="" type="checkbox"/> Carbon

Shock Bush

Front	<input checked="" type="checkbox"/> Short <input type="checkbox"/> Std.
Rear	<input type="checkbox"/> Short <input checked="" type="checkbox"/> Std. <input type="checkbox"/> Long

● Rear Upper Arm Position



<input type="checkbox"/> Plastic <input checked="" type="checkbox"/> Aluminum
--

Hub Carrier Bush	<input checked="" type="checkbox"/> Plastic <input type="checkbox"/> Brass
------------------	---

● Rear Wheel Hub

<input checked="" type="checkbox"/> Narrow <input type="checkbox"/> Std. <input type="checkbox"/> Wide
--


● Front Sus. Arm

<input type="checkbox"/> SS <input checked="" type="checkbox"/> Soft (Std.) <input type="checkbox"/> Hard

● Front Sus. Bush

Rear Side	<input type="checkbox"/> <input checked="" type="checkbox"/>
-----------	--

● Front Upper Arm Position




● Front Wheel Hub

<input type="checkbox"/> Narrow <input checked="" type="checkbox"/> Std. <input type="checkbox"/> Wide
--

● Front Hub Carrier

<input type="checkbox"/> Plastic <input checked="" type="checkbox"/> Aluminum
<input type="checkbox"/> 13° <input type="checkbox"/> 16° <input checked="" type="checkbox"/> 17.5° <input type="checkbox"/> 19° <input type="checkbox"/> 22°



● Rear Sus. Bush

Front Side	<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>
Rear Side	<input type="checkbox"/> (2.5) (2.5) <input checked="" type="checkbox"/> (3) (3) <input type="checkbox"/> (3.5) (3.5) <input type="checkbox"/> (2) (2) <input type="checkbox"/> (3) (3) <input type="checkbox"/> (3) (3)


● Rear Sus. Arm

<input type="checkbox"/> Soft (Std.) <input checked="" type="checkbox"/> Hard
Rear Sus. Bush
<input type="checkbox"/> Short <input type="checkbox"/> Medium <input checked="" type="checkbox"/> Long

● Servo Horn

Steering	Throttle
<input type="checkbox"/> Plastic <input checked="" type="checkbox"/> AL. Long <input type="checkbox"/> AL. Short	<input type="checkbox"/> Plastic <input checked="" type="checkbox"/> AL.

● Steering Plate



● Sway Bar

Front	Rear
φ 2,1mm 1 mm	φ 2,9mm 2 mm

● Weight

Front	Rear
<input type="checkbox"/> None <input type="checkbox"/> IFW604-10 <input checked="" type="checkbox"/> IFW604-20 <input type="checkbox"/> other	<input type="checkbox"/> None <input type="checkbox"/> IFW605-10 <input checked="" type="checkbox"/> IFW605-20 <input type="checkbox"/> other

● Wing

<input checked="" type="checkbox"/> IF491(TK14)	Flap <input checked="" type="checkbox"/> None <input type="checkbox"/> 5mm <input type="checkbox"/> 8mm <input checked="" type="checkbox"/> Holes
---	--

memo:

- OPTIONS:**
- titanium screws and turnbuckles
 - IFW426 aluminium AMB Plate
 - IFW474 17.5 caster blocks
 - IFW631 and IFW632 shock towers
 - center dogbones: IFW617, IFW617, MA081
 - IFW626 carbon servo saver plate
 - IFW613 front CVA driveshafts
 - IF403B and IFW634-45S small center diff