

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm
 UM511(RB5)
 UM525(WC Edition)

Shock Stay:
 UM511(RB5)
 UM525(WC Edition)

4.8mm Ball Stud:
 UM128(WC Edition)
 UMW508 (+2mm High Mount)

Camber: _____ °

Ackerman Steer Spacer: _____ mm
 LA246(WC Edition)
 UM129(Std)

4.8mm Ball Stud:
 LA246(WC Edition)
 UM129(Std)

Toe: In Out _____ °

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside _____ oz _____ g
 On the skid plate _____ oz _____ g * 1oz=28g

30/92

Caster Spacer:
 25° 0.5
 30° 1.0
 None

Axle Type:
 UM506(Std/Steel)
 UM569(WC Edition)

Axle Spacer:
 Out _____ mm
 In _____ mm

Wheelbase: Long Middle Short

Comments: _____

Rear Suspension

Shock Stay:
 UM512(RB5)
 UMW501
 UM520(RB5 SP)
 UM520S(WC Edition)

Wing Height:
 1
 2
 3

Sus Holder Spacer:
 0.5
 1.0
 None

Anti-Squat: _____ °

Sway Bar: None
 _____ mm

Lower Arm:
 UM566(WC Edition)
 UM521(SP2)

Upper Spacer: _____ mm
 Type-B (UM519)
 Type-B2 (UM519-2)

Wheelbase:
 Long
 Middle
 Short

Rear Hub add Toe:
 0° Type-B (UM519)
 0° Type-B2 (UM516-2)
 0° Alu (UMW516-0)
 0.5° Alu (UMW516-05)
 1° Alu (UMW516-1)

Upper Spacer: _____ mm

Lower Sus Holder:
 Normal RF:RB5 UMW511+UMW512
 Aluminum(Opt) UMW514+UMW515
 Narrow RF2:RB5SP UMW514+UMW515
 Wide RF2:RB5SP UMW514+UMW515

Lower Arm:
 UM566(WC Edition)
 UM521(SP2)

Camber: _____ °

Axle Spacer:
 Out _____ mm
 In _____ mm

Wheel Shaft Type:
 UM522-02(RB5 SP)
 UM510-02(RB5)

Swing Shaft:
 62.5mm:UM510,UM510-01(RB5)
 65.5mm:UM522,LA232-01(RB5 SP)

Wheel Spacer: _____ mm

Comments: _____

Editable by Am0 at PetitRC.com

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	Std:RB5 Low:ZX5FS	Std:RB5 Low:ZX5FS
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Body / Wing / Chassis


Wing: _____ **Body:** _____

Lip high: _____ **Battery Placement:**
 Front Rear

Wing Angle: 4° 7° 10° **Battery Post:**
 Pla Alu

Ride Height: F _____ mm R _____ mm

Weight Placement:



Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

Truck Condition

- | | |
|--|--------------------------------------|
| <input type="checkbox"/> Smooth | <input type="checkbox"/> Sandy |
| <input type="checkbox"/> Bumpy | <input type="checkbox"/> Soft Dirt |
| <input type="checkbox"/> Low Truction | <input type="checkbox"/> Grass |
| <input type="checkbox"/> Med. Truction | <input type="checkbox"/> Blue Groore |
| <input type="checkbox"/> Higt Truction | <input type="checkbox"/> Clay |
| <input type="checkbox"/> Wet | <input type="checkbox"/> Dusty |
| <input type="checkbox"/> Dry | <input type="checkbox"/> Other |

Kind in spring:

Soft ↑

Pink
White
Gold
Red
Yellow
Orange
Green

↓ Hard

Electronics

- Motor: _____
- Pinion/Spur: _____
- Battery: _____
- ESC: _____
- Radio: _____
- Servo: _____
- Throttle/Brake:
 EPA: _____ Expo: _____
- Initial brake: _____
- Drag brake: _____
- Throttle profile: _____
- Steering expo: _____
- Steering speed: _____

Comment : _____