

Name \_\_\_\_\_ Date \_\_\_\_\_ Truck / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension

**Upper Spacer:** \_\_\_\_\_ mm  
 UM511(RB5)  
 UM525(WC Edition)

**Shock Stay:**  
 UM511(RB5)  
 UM525(WC Edition)

**4.8mm Ball Stud:**  
 UM128(WC Edition)  
 UMW508 (+2mm High Mount)

**Camber:** \_\_\_\_\_ °

**Ackerman Steer Spacer:** \_\_\_\_\_ mm  
 LA246(WC Edition)  
 UM129(Std)

**4.8mm Ball Stud:**  
 LA246(WC Edition)  
 UM129(Std)

**Toe:**  In  Out \_\_\_\_\_ °

**Front Bulkhead Weight Placement:**  
 None  
 Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g  
 On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g

**30/92**

**Caster Spacer:**  
 25°  0.5  
 30°  1.0  
 None

**Axle Type:**  
 UM506(Std/Steel)  
 UM569(WC Edition)

**Axle Spacer:**  
 Out \_\_\_\_\_ mm  
 In \_\_\_\_\_ mm

**Bump Steer Spacer:** \_\_\_\_\_ mm

**Axle Height Spacer:**  
 Up  
 Down

**Wheelbase:**  Long  Middle  Short

**Comments:** \_\_\_\_\_

### Rear Suspension

**Shock Stay:**  
 UM512(RB5)  
 UMW501  
 UM520(RB5 SP)  
 UM520S(WC Edition)

**Wing Height:**  
 1  
 2  
 3

**Upper Spacer:** \_\_\_\_\_ mm

**Lower Sus Holder:**  
 Normal  RF:RB5  UMW511+UMW512  
 Wide  RF2:RB5SP  UMW514+UMW515

**Sus Holder Spacer:**  
 0.5  0.5  
 1.0  1.0  
 None  None

**Anti-Squat:** \_\_\_\_\_ °

**Sway Bar:**  None  \_\_\_\_\_ mm

**Lower Arm:**  
 UM566(WC Edition)  
 UM521(SP2)

**Upper Spacer:** \_\_\_\_\_ mm  
 Type-B (UM519)  
 Type-B2 (UM519-2)

**Wheelbase:**  
 Long  
 Middle  
 Short

**Rear Hub add Toe:**  
 0°Type-B (UM519)  
 0°Type-B2 (UM516-2)  
 0°Alu (UMW516-0)  
 0.5°Alu (UMW516-05)  
 1°Alu (UMW516-1)

**Camber:** \_\_\_\_\_ °

**Axle Spacer:**  
 Out \_\_\_\_\_ mm  
 In \_\_\_\_\_ mm

**Wheel Shaft Type:**  
 UM522-02(RB5 SP)  
 UM510-02(RB5)

**Swing Shaft:**  
 62.5mm:UM510,UM510-01(RB5)  
 65.5mm:UM522,LA232-01(RB5 SP)

**Wheel Spacer:** \_\_\_\_\_ mm

**Comments:** \_\_\_\_\_

Editable by Am0 at PetitRC.com

### Shock

**Shock Piston:** Front \_\_\_\_\_ Rear \_\_\_\_\_

**Shock Oil:** # \_\_\_\_\_ # \_\_\_\_\_

**Shock Spring:** \_\_\_\_\_

**Limiters:** in out mm in out mm

**Shock Length(A):** \_\_\_\_\_ mm \_\_\_\_\_ mm

**Shock Top Type:**

Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS

**5.8mm Ball End:**  
 Front:  S  M  L  
 Rear:  S  M  L

### Body / Wing / Chassis

**Wing:** \_\_\_\_\_ **Body:** \_\_\_\_\_

**Lip high:** \_\_\_\_\_ **Battery Placement:**  Front  Rear

**Wing Angle:** 4°  7°  10°  **Battery Post:**  Pla  Alu

**Ride Height:** F \_\_\_\_\_ mm R \_\_\_\_\_ mm

### Tire

Front \_\_\_\_\_ Rear \_\_\_\_\_

**Tire:** \_\_\_\_\_

**Inserts:** \_\_\_\_\_

**Wheel:** \_\_\_\_\_

**Traction Compound:** \_\_\_\_\_

### Electronics

**Motor:** \_\_\_\_\_

**Pinion/Spur:** \_\_\_\_\_

**Battery:** \_\_\_\_\_

**ESC:** \_\_\_\_\_

**Radio:** \_\_\_\_\_

**Servo:** \_\_\_\_\_

**Throttle/Brake:** \_\_\_\_\_

**EPA:** \_\_\_\_\_ **Expo:** \_\_\_\_\_

**Initial brake:** \_\_\_\_\_

**Drag brake:** \_\_\_\_\_

**Throttle profile:** \_\_\_\_\_

**Steering expo:** \_\_\_\_\_

**Steering speed:** \_\_\_\_\_

### Truck Condition

Smooth  Sandy  
 Bumpy  Soft Dirt  
 Low Truction  Grass  
 Med. Truction  Blue Groore  
 Higt Truction  Clay  
 Wet  Dusty  
 Dry  Other

### Kind in spring:

Soft ↑  
 Pink  
 White  
 Gold  
 Red  
 Yellow  
 Orange  
 Green  
 ↓ Hard