

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

Shock Stay:

 UM511(RB5)
 UM525(WC Edition)

Toe: In Out _____°

Front Bulkhead Weight Placement:

 None
 Bulkhead Inside _____ oz _____ g
 On the skid plate _____ oz _____ g * 1oz=28g

4.8mm Ball Stud:

 UM128(WC Edition)
 UMW508 (+2mm High Mount)

Caster Spacer:

 25° 0.5
 30° 1.0
 None

Camber: _____°

Axle Type:

 UM506(Std/Steel)
 UM569(WC Edition)

Axle Spacer:

 Out _____ mm
 In _____ mm

Ackerman Steer Spacer: _____ mm

4.8mm Ball Stud:

 LA246(WC Edition)
 UM129(Std)

Bump Steer Spacer: _____ mm

Axle Height Spacer:

 Up
 Down

Wheelbase: Long Middle Short

Comments: _____

Rear Suspension

Shock Stay:

 UM512(RB5)
 UMW501
 UM520(RB5 SP)
 UM520S(WC Edition)

Wing Height:

 1
 2
 3

Upper Spacer: _____ mm

Lower Sus Holder:

Normal Aluminum(Opt)

Narrow RF:RB5 UMW511+UMW512

Wide RF2:RB5SP UMW514+UMW515

Sus Holder Spacer:

 0.5 0.5
 1.0 1.0
 None None

Anti-Squat: _____°

Sway Bar: None
 _____mm

Lower Arm:

 UM566(WC Edition)
 UM521(SP2)

Upper Spacer: _____ mm

Type-B (UM519)
Type-B2 (UM519-2)

Camber: _____°

Axle Spacer:

 Out _____ mm
 In _____ mm

Wheel Shaft Type:

 UM522-02(RB5 SP)
 UM510-02(RB5)

Swing Shaft:

 62.5mm:UM510,UM510-01(RB5)
 65.5mm:UM522,LA232-01(RB5 SP)

Wheelbase:

 Long
 Middle
 Short

Rear Hub add Toe:

 0°Type-B (UM519)
 0°Type-B2 (UM516-2)
 0°Alu (UMW516-0)
 0.5°Alu (UMW516-05)
 1°Alu (UMW516-1)

Wheel Spacer: _____ mm

Comments: _____

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
	Std:RB5 Low:ZX5FS	Std:RB5 Low:ZX5FS
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Truck Condition

- | | |
|---|--------------------------------------|
| <input type="checkbox"/> Smooth | <input type="checkbox"/> Sandy |
| <input type="checkbox"/> Bumpy | <input type="checkbox"/> Soft Dirt |
| <input type="checkbox"/> Low Truaction | <input type="checkbox"/> Grass |
| <input type="checkbox"/> Med. Truaction | <input type="checkbox"/> Blue Groore |
| <input type="checkbox"/> Higt Truaction | <input type="checkbox"/> Clay |
| <input type="checkbox"/> Wet | <input type="checkbox"/> Dusty |
| <input type="checkbox"/> Dry | <input type="checkbox"/> Other |

Kind in spring:

Soft ↑	Pink
	White
	Gold
	Red
	Yellow
	Orange
	Green
↓ Hard	

Body / Wing / Chassis

Wing: _____ **Body:** _____

Lip high: _____ **Battery Placement:**

 Front Rear

Wing Angle: 4° 7° 10° **Battery Post:**

 Pla Alu

Ride Height: F _____ mm R _____ mm

Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

Comment :

Electronics

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Radio: _____

Servo: _____

Throttle/Brake:

EPA: _____ **Expo:** _____

Initial brake: _____

Drag brake: _____

Throttle profile: _____

Steering expo: _____

Steering speed: _____