

ULTIMA RB5 SP SET UP SHEET



Name **秋元 宏太**

Date **2010/6/12**

Truck / City **谷田部アリーナ**

Event **関東地区予選向け**

Front Suspension

Camber + - **1°**

Upper Spacer **1 mm**

4.8mm Ball Stud
 Standard(UM128)
 High Mount (+2mm:UMW508)

Axle Type
 Standard(Steel:UM506)
 Option(Aluminum:UMW507)

Ackerman Steer Spacer **0 mm**

Bump Steer Spacer **0 mm**

Axle Spacer
 Out(Standard) _____ mm
 In **1 mm**

Axle Height Spacer
 Up _____ mm
 Down _____ mm

Shock Stay
 Std(UM511)
 C-Comp(UMW500)

Toe In Out **0°**

Front Bulkhead Weight Placement
 None
 Bulkhead Inside _____ oz _____ g * 1oz=28g
 On the skid plate _____ oz _____ g

Caster
 25° 30°
 0.5 1.0
 None

Spacer
 0.5 1.0
 None

Comments:

Rear Suspension

Lower Sus Holder
 Normal RF:RB5 Aluminum(Opt) UMW511+UMW512
 Wide RF2:RB5SP UMW514+UMW515

Upper Spacer **3 mm**

Wheelbase
 Long
 Middle
 Short

Wing Height
 1
 2
 3

Sus Holder Spacer
 0.5 1.0
 None

Anti-Squat _____°

Swing Shaft
 62.5mm:RB5(UM510,UM510-01)
 65.5mm:RB5SP(UM522,LA232-01)

Camber + - **2°**

Axle Spacer
 Out _____ mm
 In **0.3 mm**

Wheel Shaft Type
 RB5SP(UM522-02)
 RB5(UM510-02)
 Type-B(UM519)
 Up(LA244-05)
 Middle
 Down

Wheel Spacer _____ mm

Lower Arm
 Short:RB5(UM503)
 Middle:RB5SP(UM521)

Shock Stay
 Std:RB5(UM512)
 Std C-Comp:RB5-opt(UMW501)
 Short:RB5SP(UM520)

Upper Spacer **2 mm**

Rear Hub add Toe
 0°(Standard)
 0.5°(LA244-05)

Sway Bar None _____ mm

Comments:

Shock

	Front	Rear
Shock Piston	2 - B	2 - C
Shock Oil	# 45 ※1	# 40
Shock Spring	ピンク	ピンク
Limiters	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A)	_____ mm	_____ mm
Shaft Length(B)	20 mm	28 mm
Shock Top Type	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS	
Rear Shock Body	<input checked="" type="checkbox"/> Short:RB5SP(W5196-01V)38mm <input type="checkbox"/> STD:RB5(W5187-01V)42mm	
Rear Shock Shaft	<input checked="" type="checkbox"/> STD:RB5SP(W5193-01)50mm <input type="checkbox"/> Opt:ZX5(W5183-02)54mm	

Body / Wing / Chassis

Wing
 Aquarius(LA239)
 Sagittarius(LA240)
 Aries(LA241)
 Blast-L(LA251)
 Step-L(LA247)
 Step-S(LA247)
 Blast-S(LA247)
 Other: **Step-M**

Body
 Trident:RB5(UMB01)
 Sword:RB5SP(UMB02)
 Other: _____

Weight Placement * 1oz=28g

Battery Placement
 Front Rear

Wing Angle
 4° 7° 10°

Ride Height A B **F 24.5mm R 24 mm**

Truck Condition

- | | |
|---|--|
| <input checked="" type="checkbox"/> Smooth | <input type="checkbox"/> Sandy |
| <input type="checkbox"/> Bumpy | <input type="checkbox"/> Soft Dirt |
| <input type="checkbox"/> Low Traction | <input type="checkbox"/> Grass |
| <input checked="" type="checkbox"/> Med. Traction | <input type="checkbox"/> Blue Groore |
| <input type="checkbox"/> Higt Traction | <input checked="" type="checkbox"/> Clay |
| <input checked="" type="checkbox"/> Wet | <input type="checkbox"/> Dusty |
| <input type="checkbox"/> Dry | <input type="checkbox"/> Other |

Kind in spring

- | | |
|-----|---------------|
| #55 | Orange |
| #60 | Orange Yellow |
| #65 | Yellow |
| #68 | Blue |
| #70 | Silver |
| #72 | Cobalt blue |
| #75 | Light Green |
| #80 | Green |

Tire

	Front	Rear
Tire	Bobcat	HoleShot
Inserts	Normal	Normal
Wheel	Normal	Normal
Traction Compound	F & R: クレイ	

Others

gear ratio =2.6
Motor VORTEX 8.5T
Pinion/Spur 22 78
Battery ORION5400
ESC KO BMC

Comment: ※1:ダンパーオイルとスプリングについて
 現在はオイル/スプリング共にX-GEAR製を使用。
 (※オイルはレッドを使用)