

Name Shawn Dunlap(Open Win) Date January 29-30 2011 Truck / City West Coast/ La Mirada, CA Event Reedy Race Of Champs 2011

Front Suspension

Upper Spacer 1 mm

Shock Stay
 Std (UM511)
 C-Comp (UMW500)

4.8mm Ball Stud
 Standard (UM128)
 High Mount (+2mm:UMW508)

Axle Type
 Standard (Steel:UM506)
 Option (Aluminum:UMW507)

Ackerman Steer Spacer 0 mm

Bump Steer Spacer 0 mm

Axle Spacer
 Out (Standard) _____ mm
 In _____ mm

Axle Height Spacer
 Up
 Down

Toe In Out 1 °

Front Bulkhead Weight Placement
 None
 Bulkhead Inside _____ oz 10 g
 On the skid plate _____ oz 15 g * 1oz=28g

Caster
 25°
 30°

Spacer
 0.5
 1.0
 None

Wheelbase: Long Middle Short

Comments: _____

Rear Suspension

Lower Sus Holder
 Normal RF:RB5 Aluminum(Opt) UMW511+UMW512
 Wide RF2:RB5SP UMW514+UMW515

Wing Height
 1
 2
 3

Sus Holder Spacer
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat 1 °

Swing Shaft
 62.5mm:RB5 (UM510, UM510-01)
 65.5mm:RB5SP (UM522, LA232-01)

Upper Spacer 2 mm

Wheelbase
 Long
 Middle
 Short

Rear Hub add Toe
 0° (Standard)
 0.5° (LA244-05)

Sway Bar None
 _____ mm

Upper Spacer 1 mm

Shock Stay
 Std:RB5 (UM512)
 Std C-Comp:RB5-opt (UMW501)
 Short:RB5SP (UM520)

Lower Arm
 Short:RB5 (UM503)
 Middle:RB5SP (UM521)

Wheel Shaft Type
 RB5SP (UM522-02)
 RB5 (UM510-02)
 for PL-Wheel (UMW502)

Wheel Spacer _____ mm

Axle Spacer
 Out _____ mm
 In _____ mm

Wheel Shaft Type
 Type-B (UM519)
 Up (LA244-05)
 Middle
 Down

Comments: **Used Aluminum Rear Hubs (Part Number) UMW516-0 / Inside Back Hole Used**

BB Shock

	Front	Rear
Shock Piston	<u>BB - 5Hole</u>	<u>BB - 5Hole</u>
Shock Oil	<u>#35 Losi</u>	<u>#30 Losi</u>
Shock Spring	<u>Pink (soft) Big Bore</u>	<u>Red(m-hard)</u>
Limiters	in _____ mm	in _____ mm
	out _____ mm	out _____ mm
Shock Length (A)	<u>*</u> _____ mm	<u>*</u> _____ mm
Shaft Length (B)	_____ mm	_____ mm
Shock Top Type	<input checked="" type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/>
	Std:RB5 Low:ZX5FS	Std:RB5 Low:ZX5FS
Rear Shock Body	<input checked="" type="checkbox"/> Short:RB5SP (W5196-01V) 38mm	<input type="checkbox"/> STD:RB5 (W5187-01V) 42mm
Rear Shock Shaft	<input checked="" type="checkbox"/> STD:RB5SP (W5193-01) 50mm	<input type="checkbox"/> Opt:ZX5 (W5183-02) 54mm

Body / Wing / Chassis

Wing
 Aquarius (LA239)
 Sagittarius (LA240)
 Aries (LA241)
 Blast-L (LA251)
 Step-L (LA247)
 Step-S (LA247)
 Blast-S (LA247)
 Other: _____

Body
 Trident:RB5 (UMB01)
 Sword:RB5SP (UMB02)
 Other: _____

Battery Placement
 Front Rear

Wing Angle
 4° 7° 10°

Ride Height A B F 24 mm R 23.5 mm

Tire

	Front	Rear
Tire	<u>PL Scrubs MC</u>	<u>PL Scrubs MC</u>
Inserts	<u>Stock</u>	<u>JC Bomb 1</u>
Wheel	<u>Kyosho</u>	<u>Kyosho</u>
Traction Compound		

Others

	gear ratio =2.6
Motor	<u>Orion 7.5</u>
Pinion/Spur	<u>22 / 78</u>
Battery	<u>Orion 4600</u>
ESC	<u>Tekin</u>

Truck Condition

- | | |
|----------------------------------------------------|------------------------------------------|
| <input checked="" type="checkbox"/> Smooth | <input type="checkbox"/> Sandy |
| <input type="checkbox"/> Bumpy | <input type="checkbox"/> Soft Dirt |
| <input type="checkbox"/> Low Truaction | <input type="checkbox"/> Grass |
| <input checked="" type="checkbox"/> Med. Truaction | <input type="checkbox"/> Blue Groove |
| <input type="checkbox"/> Higt Truaction | <input checked="" type="checkbox"/> Clay |
| <input checked="" type="checkbox"/> Wet | <input type="checkbox"/> Dusty |
| <input type="checkbox"/> Dry | <input type="checkbox"/> Other |

Kind in spring

#55	Orange
#60	Orange Yellow
#65	Yellow
#68	Blue
#70	Silver
#72	Cobalt blue
#75	Light Green
#80	Green

Comment: *** Long Eyelet used on rear.**