

ULTIMA RB5 SP SET UP SHEET



Name _____

Date

2009/5/24

Truck / City

谷田部アリーナ

Event

関東地区予選向け

Front Suspension

Camber + - **1** °

Upper Spacer **1** mm

4.8mm Ball Stud
 Standard(UM128)
 High Mount (+2mm:UMW508)

Shock Stay
 Std(UM511)
 C-Comp(UMW500)

Toe In Out **0** °

Front Bulkhead Weight Placement
 None
 Bulkhead Inside _____ oz _____ g * 1oz=28g
 On the skid plate _____ oz _____ g

Ackerman Steer Spacer **0** mm

Bump Steer Spacer **0** mm

Axle Type
 Standard(Steel:UM506)
 Option(Aluminum:UMW507)

Axle Spacer
 Out(Standard) **1** mm
 In _____ mm

Axle Height Spacer
 Up
 Down

Caster
 25° 30°
 0.5 1.0
 None

Comments:

Rear Suspension

Lower Sus Holder
 Normal RF:RB5 Aluminum(Opt) UMW511+UMW512
 Wide RF2:RB5SP UMW514+UMW515

Sus Holder Spacer
 0.5 1.0
 None

Anti-Squat _____ °

Swing Shaft
 62.5mm:RB5(UM510,UM510-01)
 65.5mm:RB5SP(UM522,LA232-01)

Lower Arm
 Short:RB5(UM503)
 Middle:RB5SP(UM521)

Upper Spacer **2** mm

Wheelbase
 Long
 Middle
 Short

Rear Hub add Toe
 0°(Standard)
 0.5°(LA244-05)

Sway Bar None _____ mm

Wing Height
 1
 2
 3

Upper Spacer **2** mm

Shock Stay
 Std:RB5(UM512)
 Std C-Comp:RB5-opt(UMW501)
 Short:RB5SP(UM520)

Camber + - **1** °

Axle Spacer
 Out _____ mm
 In _____ mm

Wheel Shaft Type
 RB5SP(UM522-02)
 RB5(UM510-02)
 Type-B(UM519)
 Up(LA244-05)
 Middle
 Down

Wheel Spacer _____ mm

Comments:

Shock

	Front	Rear
Shock Piston	2 - B	2 - C
Shock Oil	# 400	# 350
Shock Spring	# 55	# 68
Limiters	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A)	_____ mm	_____ mm
Shaft Length(B)	20 mm	28 mm
Shock Top Type	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS	
Rear Shock Body	<input checked="" type="checkbox"/> Short:RB5SP(W5196-01V)38mm <input type="checkbox"/> STD:RB5(W5187-01V)42mm	
Rear Shock Shaft	<input checked="" type="checkbox"/> STD:RB5SP(W5193-01)50mm <input type="checkbox"/> Opt:ZX5(W5183-02)54mm	

Body / Wing / Chassis

Wing
 Aquarius(LA239)
 Sagittarius(LA240)
 Aries(LA241)
 Blast-L(LA251)
 Step-L(LA247)
 Step-S(LA247) ※1
 Blast-S(LA247)
 Other: _____

Body
 Trident:RB5(UMB01)
 Sword:RB5SP(UMB02)
 Other: _____

Weight Placement * 1oz=28g

Battery Placement
 Front Rear

Wing Angle
 4° 7° 10°

Ride Height A B F **40** mm R **39** mm

Tire

	Front	Rear
Tire	Bobcat	Switch2.0
Inserts	Normal	Normal
Wheel	Normal	Normal
Traction Compound	F: Clay, R: Clay	

Others

gear ratio =2.6

Motor **VORTEX 7.5T**

Pinion/Spur **22 / 78**

Battery **ORION4200SHO**

ESC _____

Truck Condition

<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Traction	<input type="checkbox"/> Blue Groore
<input checked="" type="checkbox"/> Higt Traction	<input checked="" type="checkbox"/> Clay
<input checked="" type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> Other

Kind in spring

#55	Orange
#60	Orange Yellow
#65	Yellow
#68	Blue
#70	Silver
#72	Cobalt blue
#75	Light Green
#80	Green

Comment : ※1 : ウィングはフルリップからスタート