

# ULTIMA RB5 SP SET UP SHEET

**KYOSHO**  
THE FINEST RADIO CONTROL MODELS

Name \_\_\_\_\_

Date \_\_\_\_\_

Truck / City \_\_\_\_\_

Event \_\_\_\_\_

## Front Suspension

☐ 1 ☐ 2 ☐ 3  
 Upper Spacer \_\_\_\_\_ mm  
 4.8mm Ball Stud  
☐ Standard(UM128)  
☐ High Mount (+2mm:UM508)  
 Shock Stay  
☐ Std(UM511)  
☐ C-Comp(UM500)  
 Toe ☐ In ☐ Out \_\_\_\_\_ °  
 Front Bulkhead Weight Placement  
☐ None  
☐ Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g  
☐ On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g  
 Caster  
☐ 25° ☐ 30°  
 Spacer  
☐ 0.5 ☐ 1.0 ☐ None  
 Axle Type  
☐ Standard(Steel:UM506)  
☐ Option(Aluminum:UM507)  
 Axle Spacer  
☐ Out(Standard) \_\_\_\_\_ mm  
☐ In \_\_\_\_\_ mm  
 Ackerman Steer Spacer \_\_\_\_\_ mm  
 Bump Steer Spacer \_\_\_\_\_ mm  
 Axle Height Spacer  
☐ Up ☐ Down  
 Comments: \_\_\_\_\_

## Rear Suspension

### Lower Sus Holder

Normal ☐ RF:RB5 ☐ Aluminum(Opt) UM511+UM512  
 Wide ☐ RF2:RB5SP ☐ UM514+UM515  
 Sus Holder Spacer  
☐ 0.5 ☐ 0.5  
☐ 1.0 ☐ 1.0  
☐ None ☐ None  
 Anti-Squat \_\_\_\_\_ °  
 Swing Shaft  
☐ 62.5mm:RB5(UM510, UM510-01)  
☐ 65.5mm:RB5SP(UM522, LA232-01)

Editable by Am0 at PetitRC.com

☐ 1 ☐ 2 ☐ 3  
 Wing Height  
☐ 1  
☐ 2  
☐ 3  
 Upper Spacer \_\_\_\_\_ mm  
 Shock Stay  
☐ Std:RB5(UM512)  
☐ Std C-Comp:RB5-opt(UM501)  
☐ Short:RB5SP(UM520)

Upper Spacer \_\_\_\_\_ mm  
 Wheelbase  
☐ Long  
☐ Middle  
☐ Short  
 Rear Hub add Toe  
☐ 0° (Standard)  
☐ 0.5° (LA244-05)  
 Sway Bar ☐ None ☐ \_\_\_\_\_ mm  
 Axle Spacer  
☐ Out \_\_\_\_\_ mm  
☐ In \_\_\_\_\_ mm  
 Wheel Shaft Type  
☐ Type-B(UM519)  
☐ Up(LA244-05)  
☐ Middle  
☐ Down  
 Wheel Spacer \_\_\_\_\_ mm  
☐ RB5SP(UM522-02)  
☐ RB5(UM510-02)  
☐ for PL-Wheel(UM502)


Comments: \_\_\_\_\_

## Shock

### Front

### Rear

Shock Piston \_\_\_\_\_  
 Shock Oil # \_\_\_\_\_  
 Shock Spring \_\_\_\_\_  
 Limiters in out mm in out mm  
 Shock Length(A) \_\_\_\_\_ mm  
 Shaft Length(B) \_\_\_\_\_ mm  
 Shock Top Type ☐ ☐ ☐ ☐ ☐ ☐  
 Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS  
 Rear Shock Body ☐ Short:RB5SP(M5196-01V)38mm  
☐ STD:RB5(M5187-01V)42mm  
 Rear Shock Shaft ☐ STD:RB5SP(M5193-01)50mm  
☐ Opt:ZX5(M5183-02)54mm




## Body / Wing / Chassis

### Weight Placement

\* 1oz=28g

Wing  
☐ Aquarius(LA239)  
☐ Sagittarius(LA240)  
☐ Aries(LA241)  
☐ Blast-L(LA251)  
☐ Step-L(LA247)  
☐ Step-S(LA247)  
☐ Blast-S(LA247)  
☐ Other: \_\_\_\_\_  
 Body  
☐ Trident:RB5(UM501)  
☐ Sword:RB5SP(UM502)  
 Battery Placement  
☐ Front ☐ Rear  
 PL ☐



Wing Angle  
 4° ☐ 7° ☐ 10° ☐

Ride Height ☐ A ☐ B ☐ F \_\_\_\_\_ mm ☐ R \_\_\_\_\_ mm

### Tire

### Front

### Rear

Tire \_\_\_\_\_  
 Inserts \_\_\_\_\_  
 Wheel \_\_\_\_\_  
 Traction Compound \_\_\_\_\_

### Others

gear ratio =2.6

Motor \_\_\_\_\_  
 Pinion/Spur \_\_\_\_\_ / \_\_\_\_\_  
 Battery \_\_\_\_\_  
 ESC \_\_\_\_\_

## Truck Condition

☐ Smooth ☐ Sandy  
☐ Bumpy ☐ Soft Dirt  
☐ Low Traction ☐ Grass  
☐ Med. Traction ☐ Blue Groore  
☐ Higt Traction ☐ Clay  
☐ Wet ☐ Dusty  
☐ Dry ☐ Other

### Kind in spring

#55 Orange  
 #60 Orange Yellow  
 #65 Yellow  
 #68 Blue  
 #70 Silver  
 #72 Cobalt blue  
 #75 Light Green  
 #80 Green

Comment : \_\_\_\_\_