

# ULTIMA RB5 SP SET UP SHEET



Name Shin Adachi Date 11/AUG/2010 Truck / City YATABE ARENA Event \_\_\_\_\_

### Front Suspension

Upper Spacer 0.5 mm

Shock Stay  
 Std(UM511)  
 C-Comp(UMW500)

4.8mm Ball Stud  
 Standard(UM128)  
 High Mount (+2mm:UMW508)

Axle Type  
 Standard(Steel:UM506)  
 Option(Aluminum:UMW507)

Ackerman Steer Spacer  
 Low mount ball stud 0 mm

Bump Steer Spacer 0 mm

Axle Spacer  
 Out(Standard) \_\_\_\_\_ mm  
 In 1 mm

Axle Height Spacer  
 Up \_\_\_\_\_ mm  
 Down \_\_\_\_\_ mm

Camber  +  - 1 °

Toe  In  Out 1 °

Front Bulkhead Weight Placement  
 None  
 Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g  
 On the skid plate 1/2 oz 14 g

Caster Spacer  
 25 °  0.5  
 30 °  1.0  
 None

Comments: \_\_\_\_\_

### Rear Suspension

Lower Sus Holder  
 Normal  RF:RB5  Aluminum(Opt) UMW511+UMW512  
 Wide  RF2:RB5SP  UMW514+UMW515

Upper Spacer 3.25mm

Wing Height  
 1  
 2  
 3

Sus Holder Spacer  
 F  0.5  1.0  None  
 R  0.5  1.0  None

Anti-Squat \_\_\_\_\_ °

Swing Shaft  
 62.5mm:RB5(UM510,UM510-01)  
 65.5mm:RB5SP(UM522,LA232-01)

Wheelbase  
 Long  
 Middle  
 Short

Rear Hub add Toe  
 0 ° (Standard)  
 0.5 ° (LA244-05)

Sway Bar  None  \_\_\_\_\_ mm

Shock Stay  
 Std:RB5(UM512)  
 Std C-Comp:RB5-opt(UMW501)  
 Short:RB5SP(UM520)

Upper Spacer 3 mm

Axle Spacer  
 Out \_\_\_\_\_ mm  
 In \_\_\_\_\_ mm

Wheel Shaft Type  
 RB5SP(UM522-02)  
 RB5(UM510-02)  
 Type-B(UM519)  
 Up(LA244-05)  
 Middle  
 Down  
 Type-B2

Wheel Spacer  \_\_\_\_\_ mm  
 \_\_\_\_\_ mm

Lower Arm  
 Short:RB5(UM503)  
 Middle:RB5SP(UM521)

Comments: \_\_\_\_\_

### Shock

	Front	Rear
Shock Piston	2 - C	2 - C
Shock Oil	# 45 (Xgear RED)	# 40 (Xgear RED)
Shock Spring	Silver (Xgear)	Pink (Xgear)
Limiters	in _____ mm out _____ mm	in _____ mm out 0.5 mm
Shock Length(A)	_____ mm	_____ mm
Shaft Length(B)	20.0 mm	28.0 mm
Shock Top Type	<input type="checkbox"/> <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/>
Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS		
Rear Shock Body	<input checked="" type="checkbox"/> Short:RB5SP (W5196-01V) 38mm <input type="checkbox"/> STD:RB5 (W5187-01V) 42mm	
Rear Shock Shaft	<input checked="" type="checkbox"/> STD:RB5SP (W5193-01) 50mm <input type="checkbox"/> Opt:ZX5 (W5183-02) 54mm	

### Body / Wing / Chassis

Wing  
 Aquarius(LA239)  
 Sagittarius(LA240)  
 Aries(LA241)  
 Blast-L(LA251)  
 Step-L(LA247)  
 Step-S(LA247)  
 Blast-S(LA247)  
 Other: Step-M

Body  
 Trident:RB5(UMB01)  
 Sword:RB5SP(UMB02)  
 Other: \_\_\_\_\_

Battery Placement  
 Front  Rear

Wing Angle  
 4 °  7 °  10 °

Weight Placement \* 1oz=28g

Ride Height  A  B F 24 mm R 22 mm

### Truck Condition

<input type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Truction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Truction	<input type="checkbox"/> Blue Groore
<input type="checkbox"/> Higt Truction	<input type="checkbox"/> Clay
<input type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> Other

### Kind in spring

#55	Orange
#60	Orange Yellow
#65	Yellow
#68	Blue
#70	Silver
#72	Cobalt blue
#75	Light Green
#80	Green

Tire	Front	Rear	Others
Tire	_____	_____	Motor <u>ORION 2009 7.5T</u>
Inserts	_____	_____	Pinion/Spur <u>22 / 78</u>
Wheel	_____	_____	Battery <u>ORION 5400 Lipo</u>
Traction Compound	_____	_____	ESC <u>LRP SXX(1-1-1-4)</u>

Comment : Shock ball end M