

Name \_\_\_\_\_ Date \_\_\_\_\_ Track / City \_\_\_\_\_ Event \_\_\_\_\_

## Front Suspension

**Upper Spacer:** \_\_\_\_\_ mm

**Shock Tower:** \_\_\_\_\_

**Toe:**  In  Out \_\_\_\_\_ °

**Toe Rod:** \_\_\_\_\_

**Front Bulkhead Weight Placement:**

- None
- Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g
- On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g (\*1oz = 28g)

**4.8mm Ball Stud:**

- UM128 (Std)
- UMW508 (+2mm High Mount)

**4.8mm Ball Stud Spacer:** \_\_\_\_\_ mm

**Caster:**

- 25°
- 30°

**Caster Block:**

- 0.5
- 1.0
- None
- 0°
- 2°
- 4°

**AI Steering Support:**

- None
- UMW724

**Axel Spacer:**

- Out \_\_\_\_\_ mm
- In \_\_\_\_\_ mm

**Wheel Hub:**

- UM569/Std
- UM506

**Caster Block Position:**

- In (Wide/Std)
- Out (Narrow)

**4.8mm Ball Stud:**

- LA246 (-1mm Low Mount)
- 97050M (STD)

**Ackermann Steer Spacer:** \_\_\_\_\_ mm

- UMW701 Aluminum ST Plate
- UMW702 Aluminum Crank Arm

**Bump Steer Spacer:** \_\_\_\_\_ mm

**Axel Height Spacer:**

- \_\_\_\_\_ mm
- \_\_\_\_\_ mm

**Comments:** \_\_\_\_\_

**Wheelbase:** F \_\_\_\_\_ mm R \_\_\_\_\_ mm

## Rear Suspension

**Shock Position:**  Front  Rear

**Shock Tower:** \_\_\_\_\_

**RR:** \_\_\_\_\_

**Mid:** \_\_\_\_\_

**Susp Holder Spacer:**

- F  0.5  1.0  None
- R  0.5  1.0  None

**Anti-Squat:** \_\_\_\_\_ °

**4.8mm Ball Stud:**

- UM129
- UMW508 (+2mm High Mount)
- 97050M
- UM128 (Std)

**Upper Spacer:** \_\_\_\_\_ mm

**Lower Susp Holder:**

Plastic  RF  RF2L  RF2

Option  UMW511GM (RF/Alu)

(Opt/Adjustable)

- UMW705 (RF/Alu) \_\_\_\_\_ Block
- UMW725 (RF-MID/Bra) \_\_\_\_\_ Block
- UMW706 (RR-RWD) \_\_\_\_\_ Block
- UMW707 (RR-MID) \_\_\_\_\_ Block

**Universal Swing Shaft:** \_\_\_\_\_

**Camber:** \_\_\_\_\_ °

**Rear Hub Carrier:**

- 0° Type-B (UM519)
- 0° Type-B2 (UM519-2)
- 0° Alu (UMW704-0)
- 0.5° Alu (UMW704-05)
- 1° Alu (UMW704-1)

**Drive Hub:**

- 4mm (TFW113)
- 4.5mm (LAW30GM/Std.)
- 5.2mm (UMW523)

**Axle Spacer:**

- Out \_\_\_\_\_ mm
- In \_\_\_\_\_ mm

**Sway Bar:**  None  \_\_\_\_\_ mm

**Wheelbase:** F \_\_\_\_\_ mm R \_\_\_\_\_ mm

**Wheelbase:** F \_\_\_\_\_ mm R \_\_\_\_\_ mm

**Comments:** \_\_\_\_\_

## Shocks

	Front	Rear
Piston:	_____	_____
Oil:	# _____	# _____
Spring:	_____	_____
Limiters:	In _____ mm	In _____ mm
	Out _____ mm	Out _____ mm
Length (A):	_____ mm	_____ mm
O-Ring:	_____	_____
Shock Top Type:	<input type="checkbox"/> Alu (UM719/Std)	<input type="checkbox"/> UM753-1
Ball End Type:	Front <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Am0 - V4.1

## Battery placement

**Chassis:**  Stock  UM731

F \_\_\_\_\_ mm Ride Height R \_\_\_\_\_ mm

## Transmission

- Rear Motor
- Mid-Ship 3 Gear
- Mid-Ship 4 Gear
- Mid-Ship Laydown

**Battery Type**

- Straight
- Separate
- Short

Type \_\_\_\_\_

## Track Condition

- Smooth
- Bumpy
- Low Traction
- Med. Traction
- High Traction
- Wet
- Dry

- Sandy
- Soft Dirt
- Grass
- Blue Groove
- Clay
- Dusty

## Wing

Wing Mount:

- Blast-S
- Blast-L
- Step-S
- Step-M
- Step-L
- Step 2.0
- Step 3.0
- Straight
- Round

Wing Angle:

- 4°
- 7°
- 10°

Lip: \_\_\_\_\_

## Tire

	Front	Rear
Tire	_____	_____
Insert	_____	_____
Wheel	_____	_____

**Other**

Motor: \_\_\_\_\_

ESC: \_\_\_\_\_

Ratio: \_\_\_\_\_