

Name: David Poulter Date: 4-6th January 2013 Truck / City: Langenfeld, Germany Event: EOS Round 2

Front Suspension

Upper Spacer: 2.0 mm

4.8mm Ball Stud: Camber: -1.0°

☒ UM128 (Std) ☐ UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: 0.5 mm

Axle Spacer: ☐ Out 1.0 mm ☐ In 2.0 mm

Wheel Hub: mm

Bump Steer Spacer: 1.0 mm

Axle Height Spacer: ☐ 0.5 mm ☐ 1.0 mm

Toe: ☐ In ☐ Out 0.0°

Caster: ☐ 25° ☒ 30°

Spacer: ☐ 0.5 ☒ 1.0 ☐ None

Caster Block: ☒ 0° ☐ 2° ☐ 4°

Block position: ☐ IN ☒ OUT

Front Bulkhead Weight Placement: ☒ None

☐ Bulkhead Inside oz g

☐ On the skid plate oz g * 1oz=28g

Comments:

Wheelbase: F: 0.0 mm R: 1.0 mm

Rear Suspension

Sus Holder Spacer: F ☐ 0.5 ☒ 1.0 ☐ None R ☐ 0.5 ☐ 1.0 ☒ None

Anti-Squat: °

4.8mm Ball Stud: ☒ UM129 (Std) ☐ UMW508 (+2mm High Mount) ☐ 97050M

Upper Spacer: 2.0 mm

Lower Sus Holder: Normal ☐ RF ☐ Aluminum(Opt) ☒ UMW511+UMW512

Narrow ☐ Wide ☐ RF2 ☒ UMW514+UMW515

Sway Bar: ☒ None ☐ mm

Camber: -1.0°

Upper Spacer: 2.0 mm

Wheelbase: F: 2.0 mm R: 2.0 mm

Wheelbase: F: 2.0 mm R: 0.0 mm

Rear Hub add Toe: ☐ 0°Type-B (UM519) ☐ 0°Type-B2 (UM519-2) ☒ 0°Alu (UMW516-0) ☐ 0.5°Alu (UMW516-05) ☐ 1°Alu (UMW516-1)

Axle Spacer: ☐ Out mm ☐ In mm

Motor Position: ☐ Rear Motor ☒ Midship Motor

Diff.: ☐ Gear Diff. # ☒ Ball Diff.

Comments: Ali front hanger and plastic rear

Shock

Shock Piston: Kit 5 hole Kit 5 hole

Shock Oil: #500 #450

Shock Spring: Orange Yellow

Limiters: in out mm mm in out mm mm

Shock Length(A): mm mm

Shock Length(B): 20.0 mm 26.5 mm

Shock Length(C): 4.0 mm 4.0 mm

Ball End type: Front: ☒ S ☐ M ☐ L Rear: ☐ S ☐ M ☒ L

Chassis

Slipper = End flush with shaft

Screw: ☒ ☒ ☒

Ride Height: F 18 mm R 18 mm

Battery Position

Battery Type: ☐ Straight ☒ Separate ☐ Short

Battery Placement: ☒ Front ☐ Rear

Truck Condition

☒ Smooth ☐ Sandy ☐ Bumpy ☐ Soft Dirt ☐ Low Truction ☐ Grass ☐ Med. Truction ☐ Blue Groove ☒ Higt Truction ☐ Clay ☐ Wet ☐ Dusty ☒ Dry ☒ Other Wood Jumps

Wing

☐ Blast-S ☐ Wing Mount: ☐ Blast-L ☐ Narrow ☐ Step-S ☒ Wide ☐ Step-M ☐ Wing Angle: ☐ Step-L ☐ 4° ☒ 7° ☐ Step 2.0 ☐ 10°

Lip: LMR

Tire

Front: Dboats blockpass Dboats Nanobytes

Inserts: Mr O - Blue Mr O - Chubby

Wheel: Kyosho Kyosho

Traction Compound: F=A - R=A

Electronics

Motor: Orion VST 7.5

Pinion/Spur: 25/76

Battery: Orion 5500

ESC: Orion R10

Comment

Qualified C5 finished C2

Editable by Arn0 at Petitr.com