

Name: Kohta Akimoto Date: 9/30/2012 Truck / City: Yatabe Arena Event: Kanto regional series

Front Suspension

Upper Spacer: 1.5 mm

4.8mm Ball Stud: ☒ UM128 (Std) ☐ UMW508 (+2mm High Mount)

Camber: 1 °

4.8mm Ball Stud Spacer: 0 mm

Axle Spacer: ☒ Out 0.6 mm ☒ In 2.6 mm

Wheel Hub: mm

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 2.5 mm

Toe: ☐ In ☒ Out 0.5 °

Caster: ☒ 25° ☐ 30°

Spacer: ☐ 0.5 ☐ 1.0 ☒ None

Caster Block: ☐ 0° ☐ 2° ☒ 4°

Block position: ☒ IN ☐ OUT

Axle Height Spacer: ☐ mm ☒ 1.5 mm

Front Bulkhead Weight Placement: ☒ None ☐ Bulkhead Inside oz g ☐ On the skid plate oz g * 1oz=28g

Comments:

Wheelbase: F: 0 mm R: 1 mm

Rear Suspension

Sus Holder Spacer: F ☐ 0.5 ☐ 1.0 ☒ None R ☒ 0.5 ☐ 1.0 ☐ None

Anti-Squat: °

4.8mm Ball Stud: ☒ UM129 (Std) ☐ UMW508 (+2mm High Mount) ☐ 97050M

Upper Spacer: 0 mm

Lower Sus Holder: Normal ☐ RF ☐ Aluminum(Opt) ☐ UMW511+UMW512 ☐ UMW514+UMW515

Wide ☒ RF2

Sway Bar: ☒ None ☐ mm

Camber: 1 °

Axle Spacer: ☐ Out mm ☒ In 0.3 mm

Wheelbase: F: 2 mm R: 0 mm

Rear Hub add Toe: ☐ 0° Type-B (UM519) ☐ 0° Type-B2 (UM519-2) ☒ 0° Alu (UMW516-0) ☐ 0.5° Alu (UMW516-05) ☐ 1° Alu (UMW516-1)

Motor Position: ☒ Rear Motor ☐ Midship Motor

Diff.: ☐ Gear Diff. # ☒ Ball Diff.

Comments:

Shock

Shock Piston: Front 5 hole Rear 5 hole

Shock Oil: Front # 37.5 L Rear # 32.5 L

Shock Spring: Front Pink Rear Red

Limiters: in out mm in out mm

Shock Length(A): mm mm

Shock Length(B): 19.5 mm 27.0 mm

Shock Length(C): mm mm

Ball End type: Front: ☐ S ☐ M ☐ L Rear: ☐ S ☐ M ☐ L

Chassis

Screw: 3X8 Ti Screw

AMB on top of servo

On RF sus mount

3X12 Ti Screw

Use Battery holder front holes

Ride Height: F 24.5 mm R 23.5 mm

Battery Position

Battery Type: ☒ Straight ☐ Separate ☐ Short

Battery Placement: ☐ Front ☒ Rear

Tire

Front: Panther Bobcat Rear: Panther Switch2.0

Inserts: Stock Stock

Wheel: Stock Stock

Traction Compound:

Electronics

Motor: Orion 7.5T

Pinion/Spur: 21/76

Battery: Orion WTS

ESC: Much More

Truck Condition

☒ Smooth ☐ Sandy ☐ Bumpy ☐ Soft Dirt ☐ Low Truaction ☐ Grass ☒ Med. Truaction ☐ Blue Groove ☐ Higt Truaction ☒ Clay ☒ Wet ☒ Dusty ☐ Dry ☐ Other

Wing

☐ Blast-S ☐ Wing Mount : ☐ Narrow ☐ Blast-L ☐ Wide ☐ Step-S ☐ Step-M ☐ Step-L ☐ Step 2.0 ☐ Wing Angle : ☒ 4° ☐ 7° ☐ 10°

Lip : 12mm cut

Comment

No Velcro on body.

Cut front bumper so it is 30mm.

RX and Capacitor on side guards (center).