ULTIMA RT6 Setup Sheet

KYOSHO — THE FINEST RADIO CONTROL MODELS

Name	Date	Track / City	Event
ELWARD FOUAD	8&9 NOVEMBRE 2015	NEUVILLE DU POITOU	COUPE DES CHAMPIONS

Front Suspension:



Upper Spacer: 1 mm

4.8mm Ball Stud:
- [x] UM128
- [ ] UMW508 (+2mm High Mount)

Camber: 1 ° (– +)

Shock Mount: [x] IN [ ] OUT

Upper Spacer: 1 mm

4.8mm Ball Stud:
- [x] LA246 (-1mm Low Mount)
- [ ] 97050M

Ackerman Steer Spacer: 0;5 mm

Bump Steer Spacer: 2 mm

Axle Height Spacer: [x] Up [ ] Down

Axle Spacer: [x] Out 1 mm

Caster Block: [x] IN (wide/Std) [ ] OUT (Narrow) 0 °

Toe: [ ] In [ ] Out 0 °

Sus Mount: [ ] UM502 [ ] UM567 [ ] UM721

Caster: [x] 25° [ ] 30°

Spacer: [ ] 0.5 [ ] 1.0 [x] None

Wheelbase: [ ] Long [ ] Middle [x] Short

Comments:

Rear Suspension:



Sus Holder Spacer:
F [ ] 0.5 [ ] 1.0 [ ] None
R [ ] 0.5 [ ] 1.0 [ ] None

Type-B (UM519)
Type-B2 (UM519-2)

Upper Spacer: 2 mm

Wheelbase: F: ___ mm R: ___ mm

Anti-Squat: ___ °

Sway Bar: [x] None [ ] ___ mm

Camber: 1 ° (– +)

Rear Hub
- [ ] 0° Type-B (UM519)
- [x] 0° Type-B2 (UM519-2)
- [ ] 0° Alu (UMW704-0)
- [ ] 0.5° Alu (UMW704-05)
- [ ] 1° Alu (UMW704-1)

Axle Spacer: [x] Out ___ mm [ ] In ___ mm

[ ] UM788 [ ] UM706

Lower Sus Holder:
Normal: [ ] RF [x] RF2
Aluminum(Opt): Front ___ Rear ___

Upper Spacer: 1 mm

Comments:

Drive:

- [ ] Rear Motor
- [x] Midship Motor

Diff:

- [ ] Gear Diff #
- [x] Ball Diff

Shock:

	Front	Rear
Shock Piston:	stock	stock
Shock Oil:	# 45losi	# 35losi
Shock Spring:	yellow	red
Limiters:	in mm / out mm	in mm / out mm
Shock Length(A):	26 mm	35 mm

Shock Top Type: [x] Normal [ ] Alu(UM719)

5.8mm Ball End:
Front: S [x] M [ ] L [ ]
Rear: S [ ] M [x] L [ ]

Chassis:

Battery Placement: ___

Front / Rear

○ No Screw
● Screw

Weight Placement

F ___ mm Ride Height: R ___ mm

Track Conditions:

Composition: carpet
Surface:
Traction: high
Comments:

Electronics:

Motor: skyrc 7.5
Pinion/Spur: 18
Battery: thunder power 5000
ESC: skyrc TORO 120A
Radio: SANWA M12
Servo: ABSIMA
Throttle/Brake:
EPA: ___ Expo: ___
Initial brake:
Drag brake:
Throttle profile:
Steering expo:
Steering speed:

Body:

jconcepts finnisher RT6 RM

Tire:

	Front	Rear
Tire:	stagger yellow	mini spike yellow
Inserts:	schum	schum
Wheel:	stock	stock
Traction Compound:		

Material:

Screw:	[x] Steel	[ ] Titanium		
Servo Horn:	[x] Normal	[ ] Rigid(UM717)		
Pinion Gear:	[x] Steel	[ ] Aluminium		
Shock Ring:	[ ] O-ring	[x] X-ring	[ ] Red	[ ] Clear

Comment :
réglage garde au sol triangle avant parallèle au sol et cardan arrière parallèle au sol.
Q2 FINISH 3

Arn0 V1.1