

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension:

4.8mm Ball Stud:
 UM128
 UMW508 (+2mm High Mount)

Upper Spacer: _____ mm

Shock Mount:
 IN
 OUT

Camber: _____ °

Ackerman Steer Spacer: _____ mm

Bump Steer Spacer: _____ mm

Toe: In Out _____ °

Sus Mount:
 UM502
 UM567
 UM721

Caster:
 25°
 30°

Spacer:
 0.5
 1.0
 None

Upper Spacer: _____ mm

Axle Spacer:
 Out _____ mm

Caster Block:
 IN (wide/Std)
 OUT (Narrow)

Axle Height Spacer:
 Up
 Down

Wheelbase: Long Middle Short

Comments: _____

Rear Suspension:

Sus Holder Spacer:
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat: _____ °

Sway Bar: None _____ mm

Upper Spacer: _____ mm

Wheelbase:
 F: _____ mm
 R: _____ mm

Rear Hub:
 0° Type-B (UM519)
 0° Type-B2 (UM519-2)
 0° Alu (UMW704-0)
 0.5° Alu (UMW704-05)
 1° Alu (UMW704-1)

Lower Sus Holder:
 Normal Aluminum(Opt)
 RF RF2 Front _____ Rear _____

Upper Spacer: _____ mm

Comments: _____

Drive:

Rear Motor
 Midship Motor

Diff:

Gear Diff # _____
 Ball Diff _____

Shock:

	Front		Rear	
Shock Piston:	_____		_____	
Shock Oil:	# _____	# _____		
Shock Spring:	_____		_____	
Limiters:	in _____ out _____	mm _____ mm _____	in _____ out _____	mm _____ mm _____
Shock Length(A):	_____ mm		_____ mm	
Shock Top Type:	<input type="checkbox"/> Normal		<input type="checkbox"/> Alu(UM719)	
5.8mm Ball End:	Front: S <input type="checkbox"/>	M <input type="checkbox"/>	L <input type="checkbox"/>	
	Rear: S <input type="checkbox"/>	M <input type="checkbox"/>	L <input type="checkbox"/>	

Chassis:

Battery Placement: Front Rear

Weight Placement:
 No Screw
 Screw

F _____ mm Ride Height: R _____ mm

Track Conditions:

Composition: _____
 Surface: _____
 Traction: _____
 Comments: _____

Electronics:

Motor: _____
 Pinion/Spur: _____
 Battery: _____
 ESC: _____
 Radio: _____
 Servo: _____
 Throttle/Brake: _____
 E PA: _____ Expo: _____
 Initial brake: _____
 Drag brake: _____
 Throttle profile: _____
 Steering expo: _____
 Steering speed: _____

Body:

Material:

Screw: Steel Titanium
 Servo Horn: Normal Rigid(UM717)
 Pinion Gear: Steel Aluminium
 Shock Ring: O-ring X-ring Red Clear

Comment: _____

