

ULTIMA RZ6 SET UP SHEET



Name: Nick Caro Date: 11th June Track / City: Eden Park Raceway Event: BRCA National Rd3

Front Suspension:

Shock Position:

4.8mm Ball Stud: UM128(Std.) UMW508(+2mm High Mount)

Upper Spacer: 2 mm

4.8mm Ball Stud Spacer: 0 mm

Camber: -1 °

AL. Steering Support: None UMW724

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M (Std)

Ackerman Steer Spacer: 0 mm

Ackerman arrow direction: Front(std) Rear

Option: UMW701 Alu ST Plate UMW702 Alu Clank Arm

Wheel Hub: UM569 / Std UM506

Weight Placement: None Bulkhead Inside 9 On the skid plate 9

Toe: In Out 0 °

Tie Rod: _____

Front Bulkhead

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Caster Block Position: IN (wide/Std) OUT (Narrow)

Wheelbase: F: 0 mm R: 1 mm

Comments: Schelle Rack

Rear Suspension:

Shock Position:

Wing Stay Position:

Shock Stay Type: LA352(std) LAW59 (Carbom/2mmLow)

Lower Sus Holder Block: Front B-in Rear F-out

Lower Sus Holder Spacer: Front 2 pip mm Rear 1 pip mm

Comments: Shocks as kit in front of tower - UMW523GM wide rear hexes

Upper Arm Position:

4.8mm Ball Stud: 97050M(Std) UM129

Upper Spacer: 2 mm

Camber: -1 °

Sus.Arm: LA272(std) UM713B

Hub Carrier: Type-B (UM519) Type-B2 (UM519-2)

0°Type-B(UM519) 0°Type-B2(UM519-2) 0°Alu(UMW704-0) 0.5°Alu(UMW704-05) 1°Alu(UMW704-1)

Wheelbase: Front: 2 mm Rear: 4 mm 0 mm 0 mm

Sway Bar: None _____ mm

Rear Diff: Gear Diff. (Oil:# _____) (Oil weight: _____ g) Ball Diff.

Shock:

	Front	Rear
Shock Piston:	Big Bore 2 Hole (2 x 1.6mm)	Big Bore 2 Hole (2 x 1.7mm)
Shock Oil:	# <u>35wt</u>	# <u>35wt</u>
Shock Spring:	X-Gear <u>ORANGE/SH #80</u>	X-Gear <u>RED/MH #72</u>
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	<u>19</u> mm	<u>27.50</u> mm
Shock Top Type:	<input checked="" type="checkbox"/> Alu(UM719/Std) <input type="checkbox"/> UM753-1	
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L	Rear: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Chassis:

Ride Height:

Front: 20 mm Rear: A B 21 mm

Tire:

	Front	Rear
Tire:	<u>Staggers</u>	<u>Mini Spikes</u>
Inserts:	<u>Schu Med</u>	<u>Schu Med</u>
Wheel:	<u>W5029W</u>	<u>W5020W</u>
Traction Compound:	<u>Yellow</u>	<u>Yellow</u>

Electronics:

Battery: Saddle Pack Short

Battery Position: Std 8mm Front

Motor Position: Front Rear

Motor Mount Position: Std 8mm Front

Motor: VST2 7.5

Pinion/Spur: 27 / 78

Body / Wing:

Body: UMB04LW

Wing Mount: Narrow Wide

Wing Dum Height: _____ mm

Wing: LA373 -Step 3.0

Wing Angle: 4° 7° 10°

Lip Height: _____ mm

Material:

Screw: Steel Titanium

Pinion Gear: Steel Aluminium

Shock O-Ring: O-ring X-ring Red Clear

Comment : _____

Track Condition:

<input checked="" type="checkbox"/> High Traction	<input type="checkbox"/> Dry	<input type="checkbox"/> Clay
<input checked="" type="checkbox"/> Med Traction	<input type="checkbox"/> Dusty	<input type="checkbox"/> Grass
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Sandy	<input type="checkbox"/> _____
<input type="checkbox"/> Smooth	<input type="checkbox"/> Blue Groove	<input type="checkbox"/> _____
<input checked="" type="checkbox"/> Bumpy	<input checked="" type="checkbox"/> Astro turf	<input type="checkbox"/> _____
<input type="checkbox"/> Wet	<input type="checkbox"/> Blue Groove	<input type="checkbox"/> _____