

ULTIMA RZ6 SET UP SHEET



Name: Nick Caro Date: 29nd May Track / City: Southport Event: Regional

Front Suspension:

Shock Position:

4.8mm Ball Stud:
 UM128(Std.)
 UMW508(+2mm High Mount)

Upper Spacer: 2 mm

4.8mm Ball Stud Spacer: 0 mm

Camber: -1 °

AL. Steering Support:
 None
 UMW724

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 97050M (Std)

Ackerman Steer Spacer: 0 mm

Ackerman arrow direction:
 Front(std) Rear

Option:
 UMW701 Alu ST Plate
 UMW702 Alu Clank Arm

Wheel Hub:
 UM569 / Std
 UM506

Wheel Hub:
 IN (wide/Std)
 OUT (Narrow)

Toe: In Out 0 °

Tie Rod: _____

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside 9
 On the skid plate 9

Caster:
 25° 30°
 A (UM502)
 B (UM721/Std)
 B (UMW722/Brass)
 B (UMW723/Alu)
 C (UM567)

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Caster Block Position: IN (wide/Std) OUT (Narrow)

Option:
 UMW701 Alu ST Plate
 UMW702 Alu Clank Arm

Bump Steer Spacer: 0 mm

Axle Height Spacer: 1.5 mm

Wheelbase: F: 0 mm R: 1 mm

Comments: Schelle Rack

Rear Suspension:

Shock Position:

Wing Stay Position:

Shock Stay Type:
 LA352(std)
 LAW59 (Carbom/2mmLow)

Upper Arm Position:

4.8mm Ball Stud:
 97050M(Std)
 UM129

Upper Spacer: 2 mm

Hub Carrier:
 Type-B (UM519)
 Type-B2 (UM519-2)

Sus.Arm:
 LA272(std)
 UM713B

Camber: -1 °

Wheelbase: Front: 2 mm Rear: 0 mm

Lower Sus Holder Block: Front B-in Rear F-out

Lower Sus Holder Spacer: Front 2 pip mm Rear 1 pip mm

Comments: Shocks as kit in front of tower - UMW523GM wide rear hexes

Sway Bar: None _____ mm

Rear Diff:
 Gear Diff. (Oil:# _____) (Oil weight: _____ g)
 Ball Diff.

Shock:

	Front	Rear
Shock Piston:	Big Bore 2 Hole (2 x 1.6mm)	Big Bore 2 Hole (2 x 1.7mm)
Shock Oil:	# <u>30wt</u>	# <u>32.5wt</u>
Shock Spring:	X-Gear YELLOW/H #75	X-Gear RED/MH #72
Limiters:	in _____ mm out _____ mm	in <u>1.5</u> mm out _____ mm
Shock Length(A):	<u>19</u> mm	<u>27.50</u> mm
Shock Top Type:	<input checked="" type="checkbox"/> Alu(UM719/Std) <input type="checkbox"/> UM753-1	
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L	Rear: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Chassis:

Ride Height:

Front: 19 mm Rear: A B 19 mm

Tire:

	Front	Rear
Tire:	<u>Staggers</u>	<u>Mini Spikes</u>
Inserts:	<u>Schu Med</u>	<u>Schu Med</u>
Wheel:	<u>W5029W</u>	<u>W5020W</u>
Traction Compound:	<u>Yellow</u>	<u>Yellow</u>

Electronics:

Battery:
 Saddle Pack Short

Battery Position:
 Std 8mm Front

Motor Position:
 Front Rear

Motor Mount Position:
 Std 8mm Front

Motor: VST2 7.5

Pinion/Spur: 27 / 78

Body / Wing:

Body: UMB04LW

Wing Mount: Narrow Wide

Wing Dum Height: _____ mm

Wing: LA373 -Step 3.0

Wing Angle: 4° 7° 10°

Lip Height: _____ mm

Material:

Screw: Steel Titanium

Pinion Gear: Steel Aluminium

Shock O-Ring: O-ring X-ring Red Clear

Comment : _____

Track Condition:

<input checked="" type="checkbox"/> High Traction	<input type="checkbox"/> Dry	<input type="checkbox"/> Clay
<input checked="" type="checkbox"/> Med Traction	<input type="checkbox"/> Dusty	<input type="checkbox"/> Grass
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Sandy	<input type="checkbox"/> _____
<input type="checkbox"/> Smooth	<input type="checkbox"/> Blue Groove	<input type="checkbox"/> _____
<input checked="" type="checkbox"/> Bumpy	<input checked="" type="checkbox"/> Astro turf	<input type="checkbox"/> _____
<input type="checkbox"/> Wet	<input type="checkbox"/> Blue Groove	<input type="checkbox"/> _____