



Name \_\_\_\_\_ Date \_\_\_\_\_ Truck / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension:




Toe:  In  Out \_\_\_\_\_°  
 Sus Mount:  UM502  
 UM567  
 UM721

Upper Spacer: \_\_\_\_\_ mm  
 4.8mm Ball Stud:  
 UM128  
 UMW508 (+2mm High Mount)




Shock Mount:  
 IN  
 OUT



Caster Spacer:  
 25°  0.5  
 30°  1.0  
 None  None

Camber: \_\_\_\_\_°  
 - +




Upper Spacer: \_\_\_\_\_ mm

4.8mm Ball Stud:  
 LA246 (-1mm Low Mount)  
 97050M

Ackerman Steer Spacer: \_\_\_\_\_ mm

Bump Steer Spacer: \_\_\_\_\_ mm



Axle Spacer:  
 Out \_\_\_\_\_ mm


Axle Height Spacer:  
 Up  
 Down

Caster Block:  
 IN (wide/Std)  
 OUT (Narrow)


Wheelbase:  Long  Middle  Short

Comments: \_\_\_\_\_

### Rear Suspension:



UM788  UM706




Upper Spacer: \_\_\_\_\_ mm

Comments: \_\_\_\_\_

### Sus Holder Spacer:

F  0.5  1.0  None  
 R  0.5  1.0  None



Anti-Squat: \_\_\_\_\_°  
 Sway Bar:  None  \_\_\_\_\_mm

### Upper Spacer:


\_\_\_\_\_ mm

### Wheelbase:

F: \_\_\_\_\_ mm  
 R: \_\_\_\_\_ mm

### Camber:

\_\_\_\_\_°  
 - +



### Lower Sus Holder:

Normal Aluminum(Opt)  
 RF  RF2 Front \_\_\_\_\_ Rear \_\_\_\_\_

### Axle Spacer:

Out \_\_\_\_\_ mm  
 In \_\_\_\_\_ mm

### Rear Hub

0° Type-B (UM519)  
 0° Type-B2 (UM519-2)  
 0° Alu (UMW704-0)  
 0.5° Alu (UMW704-05)  
 1° Alu (UMW704-1)

### Drive:


Rear Motor  
 Midship Motor

### Diff:

Gear Diff # \_\_\_\_\_  
 Ball Diff

### Shock:

	Front		Rear	
Shock Piston:	_____	_____	_____	_____
Shock Oil:	# _____	# _____	# _____	# _____
Shock Spring:	_____	_____	_____	_____
Limiters:	in _____ out _____	mm _____ mm _____	in _____ out _____	mm _____ mm _____
Shock Length(A):	_____ mm	_____ mm	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> Normal	<input type="checkbox"/> Alu(UM719)	<input type="checkbox"/> Normal	<input type="checkbox"/> Alu(UM719)



5.8mm Ball End:  
 Front:  S  M  L  
 Rear:  S  M  L


### Chassis:

### Battery Placement:



No Screw  
 Screw

### Weight Placement



F \_\_\_\_\_ mm Ride Height: R \_\_\_\_\_ mm

### Tire:

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

### Track Conditions:

Composition: \_\_\_\_\_  
 Surface: \_\_\_\_\_  
 Traction: \_\_\_\_\_  
 Comments: \_\_\_\_\_

### Electronics:

Motor: \_\_\_\_\_  
 Pinion/Spur: \_\_\_\_\_  
 Battery: \_\_\_\_\_  
 ESC: \_\_\_\_\_  
 Radio: \_\_\_\_\_  
 Servo: \_\_\_\_\_  
 Throttle/Brake: \_\_\_\_\_  
 E PA: \_\_\_\_\_ Expo: \_\_\_\_\_  
 Initial brake: \_\_\_\_\_  
 Drag brake: \_\_\_\_\_  
 Throttle profile: \_\_\_\_\_  
 Steering expo: \_\_\_\_\_  
 Steering speed: \_\_\_\_\_

### Body:

### Material:

Screw:  Steel  Titanium  
 Servo Horn:  Normal  Rigid(UM717)  
 Pinion Gear:  Steel  Aluminium  
 Shock Ring:  O-ring  X-ring  Red  Clear

Comment: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_