

Name Jared Tebo Date Jan 2013 Truck WCRC Event Reedy

Front Suspension

Shock stay hight: .5 mm

Spacer: 0 mm

Shock Stay: LA216B(SP) LA216HB

Ride Height: 20.5 mm

Camber Angle: -1 °

Toe Angle: -1 °

Sway Bar: _____

Front Diff: Rigid Oneway Differential, Setting: Loose

Bump Steer Spacer: -1 mm LA246 Low Mount

Caster Block: 7° 10°

Sus. Holder Spacer: Front _____ Rear _____

Axle-Height Spacer: Up Down

Bellcrank Spacer: _____ mm

Rear Suspension

Shock stay hight: 0 mm

Spacer: 1 mm

Shock Stay: LA217(SP) LA217H

Wing Height: _____

Camber Angle: -1 °

Sway Bar: 1.2

Sus. Holder(RF): IN OUT A

Sus. Holder(RR): IN OUT E

Ride Height: 20.5 mm

Spacer: 1 mm

Wheel Spacer: _____ mm

Hub Spacer: F: 0 mm R: 2 mm

Rear Sus. Arm: LA272(UM566,UM521)(SP) UM521-1(1-Hole) LA255

Rear Hub add Toe: 0°Type-B(UM519) 0°Type-B2(UM516-2) 0°Alu(UMW516-0) 0.5°Alu(UMW516-05) 1°Alu(UMW516-1)

Sus. Holder Spacer: Front _____ Rear _____

Shock

| | Front | Rear |
|------------------|--|---|
| Shock Piston: | <u>4 X 55</u> | <u>4 X 55</u> |
| Shock Oil: | # <u>35</u> | # <u>25</u> |
| Shock Spring: | <u>Yellow</u> | <u>Gold</u> |
| Limiters: | in mm _____ out mm _____ | in 2.75mm _____ out mm _____ |
| Shock Length(A): | <u>19</u> mm | <u>25.5</u> mm |
| Shock Top Type: | <input type="checkbox"/> Std:RB5 <input type="checkbox"/> Low:ZX5FS | <input type="checkbox"/> Std:RB5 <input type="checkbox"/> Low:ZX5FS |
| 5.8mm Ball End: | Front: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L | Rear: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L |

Tire

| | Front | Rear |
|--------------------|-----------------|-----------------|
| Tire: | <u>Hand Out</u> | <u>Hand Out</u> |
| Inserts: | <u>Hand Out</u> | <u>Hand Out</u> |
| Wheel: | <u>AKA</u> | <u>AKA</u> |
| Traction Compound: | _____ | _____ |

Electronics

Motor: Orion 6.5

Pinion/Spur: 18/78

Battery: Orion 5500

ESC: Orion R10

Radio: KO

Servo: KO RSx one 10

Throttle/Brake: _____

EPA: 100/90 Expo: _____

Initial brake: 0

Drag brake: 0

Throttle profile: 4

Steering expo: _____

Steering speed: _____

Kind in spring

| | |
|------|--------|
| Soft | Pink |
| | White |
| | Gold |
| | Red |
| | Yellow |
| | Orange |
| Hard | Green |

Sway Bar

| | |
|-----|--------|
| 1.0 | White |
| 1.1 | Pink |
| 1.2 | Red |
| 1.3 | Orange |
| 1.4 | Yellow |
| 1.5 | Blue |
| 1.6 | Green |

Body/Wing/Other

Body: PL Bulldog

Wing: Step 2.0

Lip hight: 20mm

Wing Angle: 4° 7° 10°

Battery Post: Pla Alu

Slipper Type: Direct Separates

Slipper Sheet(F-R): Red-White Red-Red White-White

Center Post: Pla Alu

Back bone screw: F R

Comments

F&R arms 2mm short wheelbase

Carbon Top Deck LAW44

40g Weight in the rear