

LAZER ZX5 SETTING SHEET



Name 秋元 宏太 Date 2008/07/20 Truck 谷田部アリーナ Event '08全日本向け

Front Suspension

Upper Spacer 0 mm

Hub Carrier 4° 7° 10°

Axle High Spacer Up Low

Bump Steer Spacer 0 mm

Knuckle Standard Opposite

Camber Angle -1° Toe Angle 0° Sway bar 1mm

Front Diff. Rigid Oneway Diff.

Sus. Holder Spacer
Front Rear

Crank Spacer 1 mm

Ride Height 20 mm
シャーシ下で計測

Shock Piston 2B
Shock Oil # 450
Shock Spring # 65

20 mm

Rear Suspension

Upper Spacer 0 mm

Sus. Holder Front BF BR Rear A15 A25 A30

Sus. Holder Spacer Front Rear

Hub Carrier Spacer 2 mm

Hub Carrier 0° 2°

Hub Carrier Height Up ※2 Middle Down

Camber Angle -1°

Sway bar 1.2mm

Ride Height 20.5 mm
シャーシ下で計測

Shock Piston 2C
Shock Oil # 400
Shock Spring # 68

28 mm

Tire

Front Tire _____ Compound _____

Rear Tire _____

Front Inserts コンディションに応じて変更

Rear Inserts _____

Others

Motor VORTEX 6.5T Center Shaft Oneway Direct

Pinion/Spur 18 / 78 Slipper Sheet Red-White Red-Red White-White

Wing アクエリアス(2段CUT) Wing Angle 0° 7° 4°

Truck Condition

Smooth Dry

Bumpy Wet

Low Truction Dusty

Med. Truction Indoor

High Truction Outdoor

Spring Rate

#50	Black	#68	Blue
#55	Orange	#70	Silver
#60	Orange Yellow	#75	Light Green
#65	Yellow	#80	Green

Gear Ratio

Secondary Gear Ratio 2.5 (16:40)

	16	17	18	19	20	21	22	23	24	25
76		11.18	10.56	10.00	9.50	9.05	8.64	8.26	7.92	7.60
78	12.19	11.47	10.83	10.26	9.75	9.29	8.86	8.48	8.13	7.80

Shock Piston

Soft ← → Hard

2-B 2-C 2-D
3-A 3-B

Own composition (2-1.3)

Sway Bar

1.0	Nickel
1.1	Gold
1.2	Silver
1.3	Copper
1.4	Black
1.5	Golden
1.6	Chromium

Comments

※1:RハブはRB5用を使用、ボーンもRB5用に交換する

※2:バッテリー搭載位置はリヤ側