

LAZER ZX5 SETTING SHEET



Name **秋元 宏太**

Date **2008/11/16**

Truck **谷田部アリーナ**

Event **'08関東選手権向け**

Front Suspension

Upper Spacer 0 mm

Hub Carrier 4° 7° 10°

Axle High Spacer Up Low

Bump Steer Spacer 0 mm

Knuckle Standard Opposite

Camber Angle -1° Front Diff. Rigid Oneway Diff.

Toe Angle 0°

Sway bar なし

Sus. Holder Spacer
Front Rear

Crank Spacer 1 mm

Ride Height 20 mm
シャーシ下で計測

Shock Piston 2C

Shock Oil # 400

Shock Spring # 65

Rear Suspension

Upper Spacer 0 mm

Sus. Holder
Front BF BR
Rear A15 A25 A30

Sus. Holder Spacer
Front Rear

Hub Carrier Spacer 2 mm

Hub Carrier 0° 2°

Hub Carrier Height Up ※2 Middle Down

Camber Angle -1°

Sway bar 1.2mm

Ride Height 20.5 mm
シャーシ下で計測

Shock Piston 2C

Shock Oil # 350

Shock Spring # 68

Tire

Front Tire Bobcat Compound クレイ

Rear Tire Switch2.0 Compound クレイ

Front Inserts ノーマル

Rear Inserts ノーマル

Others

Motor VORTEX 6.5T

Pinion/Spur 18 / 78

Wing ステップウイング(小)

Wing Angle 0° 7° 4°

Center Shaft Oneway Direct

Slipper Sheet Red-White Red-Red White-White

Truck Condition

Smooth Dry

Bumpy Wet

Low Traction Dusty

Med. Traction Indoor

High Traction Outdoor

Spring Rate

#50	Black	#68	Blue
#55	Orange	#70	Silver
#60	Orange Yellow	#75	Light Green
#65	Yellow	#80	Green

Gear Ratio

Secondary Gear Ratio 2.5 (16:40)

	16	17	18	19	20	21	22	23	24	25
76		11.18	10.56	10.00	9.50	9.05	8.64	8.26	7.92	7.60
78	12.19	11.47	10.83	10.26	9.75	9.29	8.86	8.48	8.13	7.80

Shock Piston

Soft ← → Hard

2-B 2-C 2-D

3-A 3-B

Own composition (2-1.3)

Sway Bar

1.0	Nickel
1.1	Gold
1.2	Silver
1.3	Copper
1.4	Black
1.5	Golden
1.6	Chromium

Comments

※1: RハブはRB5用を使用、ボーンもRB5用に交換する

※2: バッテリー搭載位置はリヤ側