SET UP SHEET KYDSHO



Name 	Date	Track/City	Ev	rent
Front Suspension: Juner Arm Position: —4.8mm Ball Stud: Bump Steer Spacer: Toe:				
Shock Position: Shock Sta	n (LAW58)	_mm	eight Spacer:	Spacer: Toe:mm
		9 10/10/10/10	Block:	
Lower Sus Holder Bloc Front Rear		000) 10°	_ I3 _	Front Diff
Lower Sus Holder Space	cer: Sho	ck Position: S	us. Bush:	Front Diff:
Frontmm Rear	mm	<u></u>	☐ Wide	Gear Diff. #
Comments:		Rear mm	☐ Narrow(Std)	Ball Diff.
Rear Suspension:	Upper Arm Position:	/		Center Drive :
Shock Position:		☐ 97050M(Std) ☐ UM129		☐ Diff. Gear ☐ Slipper Clutch
1234	(1) (3) <u> </u>	Upper Spacer:mn	n	_#
0000		Н	ub Carrier:	
Shock S	bon (LAW59) ner	S. Arm: LA272		UM519-2) 0°Alu(UMW704-0) 0.5°Alu(UMW704-05) 1°Alu(UMW704-1)
Lower Sus Holder Space	Wilcelbas		│ Vheelbase:	Rear Diff:
Frontmm Rear	r mm Rear _	mm	Front: mm	Gear Diff. #
Comments:			Rear: mm	Ball Diff
Shock Piston: Shock Oil: Shock Spring: Limiters: Shock Length (A):		Chassis: Ride Heig Front mm	<i>®حرا_</i> ھ ہ	Motor: Pinion / Spur: ESC: Radio: Servo:
Shock Top Type: ☐ Alu. (U Ball End:		Tire: Fr	ont	Rear
Front: S S		Rear: Tire:		
Rear: ႘ြS		Inserts: Wheel:		
Body / Wing: Note:				
	Mount: Wing Dam I	leight:		Track Condition
		'''''		☐ Smooth ☐ Sandy
9		: mm		☐ Bumpy ☐ Soft Dirt
	rew: ☐ Steel ☐ Titanium			☐ Low Traction ☐ Grass☐ Med. Traction ☐ Blue Groove
Pinion Gear:	_			☐ High Traction ☐ Clay ☐ Wet ☐ Dusty ☐ Dry ☐ ☐