

LAZER ZX7 SET UP SHEET



Name _____ Date _____ Track/City _____ Event _____

Front Suspension:

Shock Position:

Shock Stay:

Std.
 Carbon (LAW58)
 Other _____

Lower Sus Holder Block:
 Front _____ Rear _____

Lower Sus Holder Spacer:
 Front _____ mm Rear _____ mm

Comments: _____

Upper Arm Position:

4.8mm Ball Stud:
 UM129(Std)
 97050M

Upper Spacer: _____ mm

Camber _____ °

Spacer: _____ mm

Axle-Height Spacer:
 Up
 Down

Caster Block:
 7° 13°
 10°

Sus. Bush:
 Wide
 Narrow(Std)

Shock Position:

Wheelbase: Front _____ mm Rear _____ mm

Bump Steer Spacer: _____ mm

Toe:
 In
 Out _____ °

Sway Bar:
 None
 _____ mm

Ackerman Spacer: _____ mm

Front Diff:

Gear Diff. # _____
 Ball Diff. _____

Rear Suspension:

Shock Position:

Shock Stay:

Std.
 Carbon (LAW59)
 Other _____

Wing Stay Position:

Lower Sus Holder Block:
 Front _____ Rear _____

Lower Sus Holder Spacer:
 Front _____ mm Rear _____ mm

Comments: _____

Upper Arm Position:

4.8mm Ball Stud:
 97050M(Std)
 UM129

Upper Spacer: _____ mm

Toe In: _____ °

Camber _____ °

Sus. Arm:
 LA272
 UM713B
 UM762(Std)

Hub Carrier:

Type-B (UM519)
 Type-B2 (UM519-2)

Upper Spacer: _____ mm

Sus. Bush:
 IN OUT (Std.)

Shock Position:

Wheelbase: Front _____ mm Rear _____ mm

LA272

Wheelbase: Front: _____ mm Rear: _____ mm

Center Drive :

Diff. Gear Slipper Clutch
 # _____

Sway Bar:
 None
 _____ mm

Rear Diff:

Gear Diff. # _____
 Ball Diff. _____

Shock:	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length (A):	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> Alu. (UM719) <input type="checkbox"/> UM753-1B(Std.)	
Ball End:	Front: S M L Rear: S M L	Spring Seat: Front: Rear:

Chassis:

Center Bulk:
 Front Rear (Std.)

Ride Height: _____ mm

Front _____ mm **Rear** _____ mm

Electronics:

Motor: _____

Pinion / Spur: _____

ESC: _____

Radio: _____

Servo: _____

Tire:

	Front	Rear
Tire:	_____	_____
Compound:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Note:	_____	

Body / Wing:

Body: _____

Wing Mount: Narrow Wide

Wing Dam Height: _____ mm

Wing: _____

Wing Angle: 4° 7° 10°

Lip Height: _____ mm

Comment :

Track Condition

<input type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Traction	<input type="checkbox"/> Blue Groove
<input type="checkbox"/> High Traction	<input type="checkbox"/> Clay
<input type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> _____

Material:

Screw: Steel Titanium

Pinion Gear: Steel Aluminum

Shock O-Ring: O-ring X-ring Red Clear