

Name: Reno Savoya Date: 03/12/2018 Event: _____
 City: Lyon State: France Track: _____

Track Indoor Tight Smooth Hard Packed Blue Groove Wet Low Bite High Bite
 Conditions Outdoor Open Rough Loose/Loamy Dry Dusty Med Bite Other _____

Front Suspension
 Toe: 2° out
 Ride Height: 25mm
 Camber: -2°
 Caster Block: 17.5 20
 Spindle Height: High Low
 Wheel Hex: +1
 Sway Bar: 2,3mm
 Piston/Oil: 5x1,5mm - 40wt
 Shock Type: Bladder Emulsion Vented
 Spring: EVO Purple
 Pills: A 1 down B 1 down
 Overall Shock Length: 105 mm (inside)
 Drag Link/Ackerman: Full back
 Bump Spindle: 1mm Link: 2mm
 Camber Link: 2 - B
 Shock Location: 3 - outside
 Receiver Battery Type: RC Concept 2000
 Weight: _____

Differentials
 Front: Standard Smart
 Spring Wire Dia. _____
 Qty of Springs: _____
 Ramp Plate: _____
 Grease: _____
 Diff Fluid: 15 k
 Center: Standard Smart
 Spring Wire Dia.: _____
 Qty of Springs: _____
 Ramp Plate: _____
 Grease: _____
 Diff Fluid: 7 k

Drive Shaft
 Front: CVA UNI
 Rear: CVA UNI

Arm Inserts
 Front: None Plastic Carbon
 Rear: None Plastic Carbon

Ackerman

Notes: _____

Rear Suspension
 Shocks: FWD Back Shock Shaft: 3.5 4.0
 Toe/C Pill: 0 (3°)
 Anti-Squat/C Pill: 1 up (3°)
 Ride Height: 31mm
 Camber: -2°
 Rear Hub Spacing: Full back
 Hub Height: A B Other
 Wheel Hex: +2mm
 Sway Bar: 2,7mm
 Piston/Oil: 5x1,5mm + 1x1mm - 35wt
 Shock Type: Bladder Emulsion Vented
 Spring: EVO orange
 Stroke: _____
 Overall Shock Length: 122 mm (outside)
 Camber Link: 1 - D
 Shock Position: 4 - outside
 Rear Diff Fluid: 3 k
 Weight: _____

Wing Setup

Wing Type: STOCK
 Wicker Bill: .250 .350

Notes: _____

Engine
 Engine: RC Concept MC5 world Fuel: THOR 25%
 Glow Plug: RC3 TH Head Clearance _____
 Pipe/Header: EFRA 2133 Gearing: 13/48

Clutch

Clutch Shoes and Springs Info
4 aluminium
4 gold

Tires

	Type	Compound	Insert
Front:	<u>JC Stalkers</u>	<u>Green</u>	<u>Dirt tech</u>
Rear:	_____	_____	_____
Notes:	_____		