

Setup S		Sheet	Track:			
	Driver:		Indoor	Slick	☐ Smooth	
			Outdoor	Loose-Dirt	Rough	
	Date:		_ Tight / D Open	☐ Blue-Groove	☐ Extra-Rough	
Front Suspension (Circle or Check the Appropriate Settings)  Notes:						
☐ In O ☐ Inr	ner 🛭 Outer					
Ride Height	√ ↑   □ St	1 ,7 7		<sub>1</sub>		
Camber 🗆 +	) (00) u ot	; ; _	Sway Bar I No			
□ Stock ∘			Yes size			
			# of washe	3 3		
☐ Plastic ☐ Dogb Diff ☐ Steel ☐ Drive Shafts ☐ CVD	one Aluminum  Steel	# of wash	\ /	is $\Box$	11	
Front Shocks			ers			
Oil:				Inside 3	2 1	
Piston: Standard / 🗆 [	Drilled		☐ Middl		(660	
Spring:			☐ Outside \	·		
Internal Spring: Outsi	de-		0	50		
Rear Suspension  Inside  o	Notes:					
Toe-In Outside						
Ride Height	-					
Camber 🗆 +			Sway Bar I No			
Pivot Support □ No Shim Und	er Front □ Shim U		Yes size	_		
□ Dogb	one Aluminum Steel		Hole in Rear Hub		12 1	
Diff Steel Drive Shafts Slider	rs Plastic	1		Hole in		
Rear Shocks		Hub Spacing		Bulkhead		
Oil:		☐ Forward ☐ Middle	C B A			
Piston: Standard / 🗆 [	Orilled	Back	、 <i>//⁻//</i> □ Οι	ıtside nside	2.5 2 ① 5.5 5 ④ 3 8 ⑦ 6	
Spring:				<u> </u>		
Limiters:   Inside-  Outsi	de					
Tir es	Compound	Foam		Motor:		
Front:Rear:				Pinion:		
Wing Setup:		_		Spur:		
-	I One-Way: □ Sof	t Spring				
Slipper:    Yes    No						
	orward 🗖 Other:					
Notes:						