



SETUP SHEET

Track: General Grass Setup

Driver: Richard Cree

Date: 1/21/04

Indoor
 Outdoor

Slick
 Loose Dirt
 Blue-Groove

Smooth
 Rough
 Extra-Rough

Tight / Open

FRONT SUSPENSION

(Circle or Check the Appropriate Settings)

XX Standard 42F 42R
Overdrive 41F 42R
Underdrive 42F 41R

In _____ °
Toe Out 0

Pivot Support: 5F(5°), 7.5F(7.5°), 10F(10°)

Ride Height Bones/Arms between

Front Drive:

Diff

One-Way

Drive Shafts

Dogbone Aluminum
 CVD Steel

Camber - _____ °
 + 1

Diff Plastic
 Steel

of washers

2

3
 2
 1

Caster Stock _____ °
 Other _____

Sway Bar No
 Yes size _____

of washers under steering/
tie-rod ball studs

Spindle ball stud: 0

Bellcrank ball stud: 0

Hole # 1

Outside Inside

Front Shocks

Oil: 35 Losi oil

Piston: 55 Standard / Drilled

Spring: Black

Internal Spring: no

Limiters: Inside- .120 Outside- _____

Notes:

REAR SUSPENSION

Pivot Support: -IR (-1°), IR (1°), 3R (3°)

Toe-In Inside 2 °
 Outside _____ °

Ride Height Chassis level with front

Camber - _____ °
 + 1

Diff Plastic Steel
 Dogbone CVD Sliders Aluminum Steel Plastic

Drive Shafts

No

Sway Bar Yes size _____

Hub Spacing

Forward
 Middle
 Back

Outside

Inside

Rear Shocks

Oil: 30 Losi oil

Piston: 55 Standard / Drilled

Spring: Red

Limiters: Inside .120 Outside- 0

Notes:

Tires:

Compound

Foam

Front: Schumacher Minispike Yellow

Losi 4wd firm

Rear: Schumacher Minispike Yellow

Losi 4wd firm

Wing Setup: _____

Motor: 10x2 Peak

Pinion: 18

Spur: 94

Battery Placement: Back Forward Other: _____

Transponder Position: _____

Notes: Cut outer and inner pins off of front tires.