



SETUP SHEET

Track: Simbach/Munich

Driver: Marcus Lubke

Date: 6/29/03

Indoor
 Outdoor

Slick
 Loose Dirt
 Blue-Groove

Smooth
 Rough
 Extra-Rough

Tight / Open

FRONT SUSPENSION

(Circle or Check the Appropriate Settings)

x Standard 42F 42R
Overdrive 41F 42R
Underdrive 42F 41R

In Out 1/2

Pivot Support: 5F(5°), 7.5F(7.5°), 10F(10°)

Ride Height Chassis Level

Front Drive:

Diff
 One-Way

Drive Shafts

Dogbone Aluminum
 CVD Steel

Camber - + 1

Diff Plastic
 Steel

of washers

1

3
 2
 1

Caster Stock Other

Sway Bar No Yes size

of washers under steering/
tie-rod ball studs

Spindle ball stud: 0

Bellcrank ball stud: 0

Hole # 4

Outside Inside

Front Shocks

Oil: 35

Piston: 57 Standard / Drilled

Spring: Orange

Internal Spring: Yes

Limiters: Inside- Spring Outside-

Notes:

REAR SUSPENSION

Pivot Support: -IR(-1°), IR(1°), 3R(3°)

Toe-In Inside 2
 Outside 1

Ride Height Arms level

Camber - + 1

Diff Plastic Steel
 Dogbone Aluminum
 CVD Steel
 Sliders Plastic

Drive Shafts

No

Sway Bar Yes size

Hub Spacing

Forward
 Middle
 Back

Outside

Inside

Rear Shocks

Oil: 35

Piston: 54 Standard / Drilled

Spring: Yellow

Limiters: Inside .260 Outside-

Notes:

Tires:

Compound

Foam

Front: Blockhead

Red

Rear: X-2000

Red

Wing Setup: _____

Motor: Orion 10x2

Pinion: 18

Spur: 92

Battery Placement: Back Forward Other: _____

Transponder Position: Behind motor

Notes: _____