



SETUP SHEET

Track: General

Driver: Jukka Steenari

Date: 11/21/02

- Indoor
- Outdoor
- Tight / Open

- Slick
- Loose Dirt
- Blue-Groove

- Smooth
- Rough
- Extra-Rough

FRONT SUSPENSION

(Circle or Check the Appropriate Settings)

In Out 0

Pivot Support: 5F(5°), 7.5F(7.5°), 10F(10°)

- x Standard 42F 42R
- Overdrive 41F 42R
- Underdrive 42F 41R

Ride Height Bones above level

Front Drive:
 Diff
 One-Way

Drive Shafts

- Dogbone Aluminum
- CVD Steel

Camber - + 1

Diff Plastic Steel

of washers

.060

- 3
- 2
- 1

Caster Stock Other

of washers under steering/tie-rod ball studs

Spindle ball stud: .060

Bellcrank ball stud: 0

Hole # 1

Outside Inside

Front Shocks

Oil: 25

Piston: 667 Standard / Drilled

Spring: Green

Internal Spring: no

Limiters: Inside- 0 Outside- 0

Notes:

Front Aluminum CVD Kit P/N-LOSA9967(Coming soon)
Front Oneway P/N-LOSA3245

REAR SUSPENSION

Pivot Support: -IR(-1°), IR(1°), 3R(3°)

Toe-In Inside 2
 Outside 1

Ride Height Arms level

Camber - +

Diff Plastic Steel Dogbone Aluminum CVD Steel Sliders Plastic

Drive Shafts

No

Sway Bar Yes size

Hub Spacing

- Forward
- Middle
- Back

B A

Outside

Inside

- 3
- 2
- 1

- 3
- 2
- 1

Rear Shocks

Oil: 35

Piston: 442 Standard / Drilled

Spring: Yellow

Limiters: Inside .100 Outside- "A"+"B"

Notes:

Rear Aluminum CVD Kit P/N-LOSA9966(Coming Soon)
Rear Sway Bar Kit P/N-LOSA4257(Coming soon)
1 Degree XXX Hubs-LOSA9807

Tires:

Compound

Foam

Front: Taper Pin

Red

Standard

Rear: Taper Pin

Red

Standard

Wing Setup:

Motor: Orion 9x1

Pinion: 18

Spur: 92

Battery Placement: Back Forward Other:

Transponder Position:

Notes: