



SETUP SHEET

Track: French Nats Rd2 Reims

Driver: Carl Maignien

Date: 12-13/04/2008

- Indoor
- Outdoor

- Slick
- Loose Dirt
- Blue-Groove

- Smooth
- Rough
- Extra-Rough

- Tight / Open

FRONT SUSPENSION

(Circle or Check the Appropriate Settings)

In
Toe Out 0°

Ride Height Dogbones level

Camber - 1°
 +

Caster Stock
 Other

Sway Bar No
 Yes size

Pivot Support: 5F(5°), 7.5F(7.5°), 10F(10°)

Front Drive:

- Diff
- One-Way

Plastic

Diff Steel

Ackerman:

- Forward
- Back

Drive Shafts

Standard 42F 42R

Overdrive 41F 42R

Underdrive 42F 41R

- Dogbone Aluminum
- CVD Steel

of washers under steering/
tie-rod ball studs

Spindle ball stud: _____

Bellcrank ball stud: _____

of washers

0

Hole # 1

- Outside
- Inside

Front Shocks

Oil: 30

Piston: Pink Standard / Drilled

Spring: Silver

Internal Spring: _____

Limiters: Inside- 1 mm Outside-

Notes:

REAR SUSPENSION

Pivot Support: -IR(-1°), IR(1°), 3R(3°)

Toe-In Inside _____
 Outside _____

Ride Height Dogbones level

Camber - 1°
 +

Diff Plastic Steel
 Dogbone Aluminum
 CVD Steel
 Sliders Plastic

Drive Shafts

No

Sway Bar Yes size

Hub Spacing

- Forward
- Middle
- Back

- B
- A
- Outside
- Inside

Rear Shocks

Oil: 25

Piston: Pink Standard / Drilled

Spring: Yellow

Limiters: Inside 3 mm Outside-

Notes:

Tires: _____ Compound _____ Foam _____

Front: Losi Ifmar StudRed

Rear: Losi Ifmar Stud Red

Wing Setup: Large Wing

Motor: 5.5

Pinion: 18

Spur: 82

Battery Placement: Back Forward Other: _____

Transponder Position: _____

Notes: _____

