



Setup Sheet

Driver: _____

Date: _____

Track: _____

☐ Indoor

☐ Outdoor

☐ Tight / ☐ Open

☐ Smooth

☐ Rough

☐ Slippery

☐ High-Bite

☐ Blue-Groove

FRONT SUSPENSION (Circle or Check the Appropriate Settings)

Toe ☐ In _____°
☐ Out _____°

Ride Height _____

Camber ☐ - _____°
☐ + _____°

Caster ☐ Stock _____°
☐ Other _____°

Sway Bar ☐ No
☐ Yes size: _____

of washers under steering / tie-rod ball studs

Spindle ball stud: _____

Bellcrank ball stud: _____

Spindle Location

☐ Top
☐ Middle
☐ Bottom

☐ A
☐ B
☐ C

☐ Long
☐ Short

☐ Long
☐ Short

☐ Outside
☐ Inside

☐ 4

☐ 3

☐ 2

☐ 1

of washers under ball stud

☐ 1

☐ 2

☐ 3

☐ Inside
☐ Middle
☐ Outside

Front Shocks

Oil: _____

Piston: _____ ☐ Standard / ☐ Drilled

Spring: _____ Internal: ☐ Yes / ☐ No

Limiters: ☐ Inside- _____ ☐ Outside- _____

REAR SUSPENSION

Body: _____

Toe-In ☐ Inside _____°
☐ Outside _____°

Spoiler: _____

Pivot Support ☐ No Shim
☐ Shim Under Front — # of shims: _____

1 Shim = 1°

Ride Height _____

Camber ☐ - _____°
☐ + _____°

Drive Shafts ☐ Dogbones ☐ Aluminum
☐ CVDs ☐ Steel

Rear Hub Spacing ☐ Forward
☐ Center
☐ Rear

Sway Bar ☐ No
☐ Yes size: _____

Rear Shocks

Oil: _____

Piston: _____ ☐ Standard / ☐ Drilled

Spring: _____ Internal: ☐ Yes / ☐ No

Limiters: ☐ Inside- _____ ☐ Outside- _____

☐ 4

☐ 3

☐ 2

☐ 1

☐ 1

☐ 2

☐ 3

☐ Short
☐ Long

☐ Outside
☐ Middle
☐ Inside

☐ Outside
☐ Inside

☐ Long
☐ Short

Tires

Compound

Foam

Front: _____

Rear: _____

Motor: _____ Pinion/Spur: ____ / ____

Battery Position: _____

Weather Conditions/Notes: _____