

SETUP SHEET



		100					2-13-5
Name:			ate:			Event:	
City:	State:		rack:				
Track ☐ Indoor ☐ Tight ☐ Smooth Conditions ☐ Outdoor ☐ Open ☐ Rough	☐ Hard Packed ☐ Blue Gro		Wet Dusty	□ Low Bite □ Med Bite			
Front Suspension					<u> </u>		1 — ¬
Toe:				Rack 1	Гуре	Bellcrank Typ	e 2
Ride Height:					- L		4
Camber:			_		6	//\	
Caster:			_	-		/ Inside Outside	
Sway Bar:							
Oil:							
Piston:				,	A		
Spring:			_	Č	C	Inside — Middle —	2
Limiters:						Outside _	3———
Spindle Height:			—				
Axle Spacer:							•
Axle Spacer Size:					P	- Short	6
Steering Type:						— Long	
Bump Steer:				lotes:			
Camber Link:							
Shock Location:							
VLA:							
Rear Suspension							
Toe:			_				3
Pivot Support:							1-11
Ride Height:							
Camber: Rear Hub Spacing:							// //
Drive Shafts/Outdrives:					0 8 A		
Sway Bar:					© ® Ø		
Oil:						Outside Middle	(4320
Piston:				_		Inside	(0000)
Spring:							
Limiters:			— mo				
Camber Link:				4	Po	C ₁₁	B
Shock Location:					L Sh	ort	
VLA:			_ % Am ►	lotes:			
Wing Width & Height:				-			
Body Type:			Brian F				
Battery Position:			_				
Weight Placement	Tires: Type	Com	poun	d Inse	ert	Additive	Motor:
(Mark with "X")	Front:		-				Spur:
	Rear:						Pinon:
	Notes:						
Weight of							