



| Name: | Date: Event: |
|---|--|
| City: State: | Track: |
| Track Indoor Tight Smooth Hard Packed Blue Groove | • |
| Front Suspension | 17 |
| Toe: | 3_7 |
| Ride Height: | |
| Camber: | |
| Caster: 🗖 0° 🗖 3° 🗖 5° 🗖 10° | |
| Kick Angle: 🔲 20° 🔲 25° 🔲 30° | SPACER SPACER |
| Sway Bar: | — SPACER |
| Oil: | |
| Piston: | OUTSIDE |
| Spring: | |
| Spindle Type: □ Inline □ Trailing | |
| Shock Limiters: | X [] |
| Shock Location: | <u> </u> |
| Bump Steer: | |
| Camber Link: | |
| | |
| Rear Suspension | |
| Chassis Configuration: ☐ Rear Motor ☐ Mid Motor | |
| Toe: | — CBA 3 |
| Anti-Squat: | |
| Roll Center: 🗖 Low Roll Center (LRC) 📮 High Roll Center | (HRC) SPACERS SPACERS 1 |
| Ride Height: | |
| Camber: | E D 2 |
| Rear Hub Spacing: | // |
| Hex Width: | - INSIDE |
| Sway Bar: | |
| Oil: | |
| Piston: | Electronics Timing Advances |
| Spring:Shock Limiters: | Timing Advance: Radio: Throttle/Brake Expo: |
| Camber Link: | Servo: Servo Expo: |
| Shock Locations: | ESC: Throttle/Brake EPA: |
| Wing/Wickerbill: | Initial Brake: Motor: Spur: Spur: |
| Battery Position: | Throttle Profile: Battery: |
| Weight Placement Tires | Compound Insert Additive |
| | |
| Rear: | |
| Notes: | |
| Weight of each piece oz./g | |