



Name:	Date:	Event:
City: State:	Track:	
Track Indoor Tight Smooth Hard Packed Blue Groove Conditions Outdoor Open Rough Loose/Loamy Dry		Low Bite High Bite Med Bite Other
Front Suspension		17
Toe:		37
Ride Height:		
Camber:		
Caster: □ 0° □ 3° □ 5° □ 10°		
Kick Angle: 🗖 20° 🗖 25° 🗖 30°		
Sway Bar:	SPACER	SPACER SPACER
Oil:		INSIDE -
Piston:		MIDDLE- OUTSIDE-
Spring:		
Spindle Type: 🗖 Inline 🚨 Trailing		
Shock Limiters:		
Shock Location:	SPACER	
Bump Steer:		
Camber Link:		
Rear Suspension Chassis Configuration: ☐ Rear Motor ☐ Mid Motor		
Toe:	6.0	
Anti-Squat:	СВ, 	3 2
Roll Center: Low Roll Center (LRC) High Roll Center (HRC) SPACERS	SPACERS 1
Ride Height:	E	
Camber:		
Rear Hub Spacing:	()	COUTSIDE
Hex Width:	- Auto at Pr	/ INSIDE
Sway Bar:		
Oil:	table	
Piston:	<u>—</u>	
Spring:	Electronics	Timing Advance:
Shock Limiters:	Radio:	Throttle/Brake Expo:
Camber Link:	Servo:	
Shock Locations:	Initial Brake:	Motor:
Wing/Wickerbill:	Drag Brake: Throttle Profile:	Pinion: Spur:
Battery Position:		·
Weight Placement Tires	Compound	Insert Additive
(Mark with "X") Front:		
Rear:		
Weight of Notes:		
each piece oz./g		