



Name:	Date: Event:
City: State:	Track:
Track Indoor Tight Smooth Hard Packed Blue Groove	•
Front Suspension	17
Toe:	3_7
Ride Height:	
Camber:	
Caster: 🗖 0° 🗖 3° 🗖 5° 🗖 10°	
Kick Angle: 🔲 20° 🔲 25° 🔲 30°	SPACER SPACER
Sway Bar:	— SPACER
Oil:	
Piston:	OUTSIDE
Spring:	
Spindle Type: □ Inline □ Trailing	
Shock Limiters:	X []
Shock Location:	<u> </u>
Bump Steer:	
Camber Link:	
	<del></del>
Rear Suspension	
Chassis Configuration: ☐ Rear Motor ☐ Mid Motor	
Toe:	— CBA 3
Anti-Squat:	
Roll Center: 🗖 Low Roll Center (LRC) 📮 High Roll Center	(HRC) SPACERS SPACERS 1
Ride Height:	
Camber:	E D 2
Rear Hub Spacing:	// / / / / / / / / / / / / / / / / / / /
Hex Width:	- INSIDE
Sway Bar:	
Oil:	
Piston:	Electronics Timing Advances
Spring:Shock Limiters:	Timing Advance:  Radio: Throttle/Brake Expo:
Camber Link:	Servo: Servo Expo:
Shock Locations:	ESC: Throttle/Brake EPA:
Wing/Wickerbill:	Initial Brake: Motor: Spur: Spur:
Battery Position:	Throttle Profile: Battery:
Weight Placement Tires	Compound Insert Additive
Rear:	
Notes:	
Weight of each piece oz./g	