



Name:	Date: Event:
City: State:	Frack:
Track ☐ Indoor ☐ Tight ☐ Smooth ☐ Hard Packed ☐ Blue Groove Conditions ☐ Outdoor ☐ Open ☐ Rough ☐ Loose/Loamy ☐ Dry	□ Wet □ Grass □ Low Bite □ High Bite □ Dusty □ Astro Turf □ Med Bite □ Other
Front Suspension	17
Toe:	
Ride Height:	
Camber:	
Caster: □ 0° □ 3° □ 5° □ 10°	
Kick Angle: ☐ 20° ☐ 25° ☐ 30°	SPACER
Sway Bar:	SPACER SPACER
Shock Type: Bladder Emulsion Oil:	INSIDE 7
Piston:	OUTSIDE -
Spring:	
Shock Limiters:	
Shock Location:	SPACER
Bump Steer:	_
Camber Link:	Notes:
Rear Suspension	- -
Chassis Configuration: Rear Motor Mid Motor	
Differential: ☐ Ball Diff ☐ Gear Diff Gear Diff Fluid:	
Toe:	— CBA 3
Anti-Squat:	
Roll Center: 🔲 Low Roll Center (LRC) 🔲 High Roll Center (HR	C) SPACERS SPACERS
Ride Height:	
Camber:	E D 2
Rear Hub Spacing:	— Jourside
Hex Width:	
Sway Bar:	
Shock Type: Bladder Emulsion Oil:	
Piston:	
Spring:	Electronics Timing Advance:
Shock Limiters:	Radio: Throttle/Brake Expo: Servo: Servo Expo:
Camber Link:	ESC: Throttle/Brake EPA:
Shock Locations:	Initial Brake: Motor: Spur: Spur:
Spoiler:	Throttle Profile: Battery:
Battery Position:	Compound Insert Additive
Weight Placement Tires (Mark with "X") Front:	Compound Insert Additive
Weight of each piece oz./g	