

**Driver and Event**  
**Name** Jesper Rasmussen  
**Date** 01 June 13  
**Event** DRCMU rd. 3  
**Weather** Sunny  
**Result** TQ 1st

**Track Conditions**  
**Surface** Outdoor Carpet  
**Grip Level** Medium  
**Track Condition** Bumpy



**Electrics and Gearing**  
**E.S.C** HobbyWing v3  
**Servo** Savox  
**Receiver** Sanwa  
**Batteries** Gens Ace  
**Motor** Thunder Power 7.5  
**Spur Gear** 98T  95T   
**Pinion** 19  
**LH Cell Position**  
 Forward  Backward

**Wheels and Tyres**  
**Rear Wheels** Flexlite  
**Rear Tyre** Schu. Minipin Yellow  
**Rear Insert** Schu. medium  
**Front Wheels** Flexlite  
**Front Tyre** Schu. Minipin Yellow  
**Front Insert** Schu. Medium

**Additional Settings**  
**Car Weight** 1800  
**Weights Added**  
**Chassis** Alloy  Option

**NOTES**  
 Core-rc oil

**Diff Type**

		<b>Diff Oil</b>
Front	Ball <input type="checkbox"/> Gear <input checked="" type="checkbox"/>	5000
Rear	Ball <input type="checkbox"/> Gear <input checked="" type="checkbox"/>	2000

**Rear Shocks**

Oil 400 Spring 2,5 Shock Cap Sealed   
 Vented  Emulsion

Piston 3  
 Drilled  Hole Size 1,6 mm

Shock Length 97 mm

**Front Shocks**

Oil 500 Spring Losi black Shock Cap Sealed   
 Vented  Emulsion

Piston 3  
 Drilled  Hole Size 1,75 mm

Shock Length 82,5 mm

**Rear Suspension**

Anti roll bar No  1.00  1.20  1.40  1.60

Wheelbase Short  Med  Long

**Rear Toe-in & Track Washers**

0.00 Difference = 0.00° Toe-in   
 0.50 Difference = 0.60° Toe-in   
 1.00 Difference = 1.30° Toe-in   
 1.50 Difference = 1.95° Toe-in   
 2.00 Difference = 2.60° Toe-in   
 2.50 Difference = 3.25° Toe-in   
 3.00 Difference = 3.90° Toe-in

Rear mm Front 0,5 mm

Blocks Moulded  Alloy

Camber at Ride Height 1,5 Deg  
 Ride Height 19,5 mm

**Anti-squat Washers**

0.00 Difference = 0.00° Toe-in   
 0.50 Difference = 0.60° Toe-in   
 1.00 Difference = 1.30° Toe-in   
 1.50 Difference = 1.95° Toe-in   
 2.00 Difference = 2.60° Toe-in   
 2.50 Difference = 3.25° Toe-in   
 3.00 Difference = 3.90° Toe-in

Rear mm Front mm

33.5 (1 Dink)   
 38.0 (2 Dink)   
 42.5 (3 Dink)

Pin High R  F   
 Pin Low

Link Washers 2 mm

**Front Suspension**

Anti roll bar No  1.00  1.20  1.40  1.60

Track Washers 1 mm

Blocks Moulded  Alloy

Camber at Ride Height 1,5 Deg  
 Ride Height 19,5 mm  
 Toe-In 0 Deg

Link Washers 0 mm

Washers 0 mm

33.5 (1 Dink)   
 38.0 (2 Dink)   
 42.5 (3 Dink)

Front Yoke  
 12.5  (Kit)  7.5

Front Rake  
 10.0 Deg  7.5 Deg