

Driver and Event		Track Conditions			
Name Tom Cockerill		Surface Clay/Concrete			
Date July '13		Grip Level Medium/High			
Event Euro's 13		Track Condition Bumpy			
Weather Dry/Hot				Additional Settings	
Result B Final				Car Weight	
Electrics and Gearing		Wheels and Tyres		Weights Added None	
E.S.C Nosram Comet HD		Rear Wheels Schumacher FlexLite		Chassis Alloy ☒ Option ☐	
Servo Spektrum		Rear Tyre PL Holeshoot		NOTES Core RC Springs & Oil Big Bore Shocks 2.0mm in Ackerman	
Reciever KO		Rear Insert PL 2 Stage			
Batteries Nosram 5800 Saddle		Front Wheels Schumacher FlexLite			
Motor Nosram Pure 2 7.5		Front Tyre PL Holeshoot			
Spur Gear 98T ☒ 95T ☐		Front Insert PL 2 Stage			
Pinion 19		Diff Type		Diff Oil	
LH Cell Position		Front Ball ☐ Gear ☒		10k	
Forward ☐ Backward ☒		Rear Ball ☐ Gear ☒		10k	

Rear Shocks		Shock Cap Sealed ☐		Front Shocks		Shock Cap Sealed ☐	
Oil 200	Spring Red	Vented ☐	Emulsion ☒	Oil 400	Spring Red	Vented ☐	Emulsion ☒
Piston 2 Hole				Piston 2 Hole			
Drilled ☒ Hole Size 1.80 mm		Shock Length 97.9 mm		Drilled ☒ Hole Size 1.70 mm		Shock Length 84.8 mm	

Rear Suspension		Anti-squat Washers	
Anti roll bar No ☒ 1.00 ☐ 1.20 ☐ 1.40 ☐ 1.60 ☐ Wheelbase Short ☐ Med ☒ Long ☐ Rear Toe-in & Track Washers 0.00 Difference = 0.00° Toe-in ☐ 0.50 Difference = 0.60° Toe-in ☐ 1.00 Difference = 1.30° Toe-in ☐ 1.50 Difference = 1.95° Toe-in ☐ 2.00 Difference = 2.60° Toe-in ☐ 2.50 Difference = 3.25° Toe-in ☒ 3.00 Difference = 3.90° Toe-in ☐ Rear 2.5 mm Front 0 mm 		Camber at Ride Height -2.0 Deg Ride Height 21 mm 0.00 Difference = 0.00° Toe-in ☐ 0.50 Difference = 0.60° Toe-in ☒ 1.00 Difference = 1.30° Toe-in ☐ 1.50 Difference = 1.95° Toe-in ☐ 2.00 Difference = 2.60° Toe-in ☐ 2.50 Difference = 3.25° Toe-in ☐ 3.00 Difference = 3.90° Toe-in ☐ Rear 2.0 mm Front 1.5 mm 	
Blocks Moulded ☐ Alloy ☒ Rear Hub Carrier Alloy ☐ Std ☒ Alloy Hub Carrier +1° ☐ -1° ☐		33.5 (1 Dink) ☐ 38.0 (2 Dink) ☒ 42.5 (3 Dink) ☐ Pin High R ☒ F ☒ Pin Low R ☐ F ☐ Link Washers 1.0 mm 	

Front Suspension		Washers 2.0 mm	
Anti roll bar No ☒ 1.00 ☐ 1.20 ☐ 1.40 ☐ 1.60 ☐ Camber at Ride Height -2.0 Deg Ride Height 21 mm Track Washers 1.0 mm 		Toe-In -1 Deg Link Washers 2.0 mm Front Yoke 12.5 ☐ (Kit) ☐ 7.5 ☒ Front Rake 10.0 Deg ☒ 7.5 Deg ☐ 	
Blocks Moulded ☐ Alloy ☒ 33.5 (1 Dink) ☐ 38.0 (2 Dink) ☐ 42.5 (3 Dink) ☒			