

Driver and Event		Track Conditions			
Name Tom Cockerill		Surface Cork Type Floor			
Date Mar '13		Grip Level Medium/Low			
Event Worksop		Track Condition			
Weather N/A				Additional Settings	
Result 3rd					
Electrics and Gearing		Wheels and Tyres		NOTES CF Chassis (U4159) Core RC Springs & Oil 2.0mm Ackerman Spacing	
E.S.C Speed Passion Reventon Pro		Rear Wheels Schumacher FlexLite			
Servo GM		Rear Tyre Schumacher MiniPin			
Receiver KO		Rear Insert Schumacher Medium			
Batteries Speed Power 4200		Front Wheels Schumacher FlexLite			
Motor Speed Passion 6.5R		Front Tyre Schumacher MiniPin			
Spur Gear 98T <input checked="" type="checkbox"/> 95T <input type="checkbox"/>		Front Insert Schumacher Medium			
Pinion 20		Diff Type			
LH Cell Position		Diff Oil			
Forward <input checked="" type="checkbox"/> Backward <input type="checkbox"/>		Front Ball <input checked="" type="checkbox"/> Gear <input type="checkbox"/>			
		Rear Ball <input checked="" type="checkbox"/> Gear <input type="checkbox"/>			

Rear Shocks		Shock Cap Sealed <input type="checkbox"/>		Front Shocks		Shock Cap Sealed <input type="checkbox"/>	
Oil 400	Spring Green	Vented <input type="checkbox"/>	Emulsion <input checked="" type="checkbox"/>	Oil 450	Spring Red	Vented <input type="checkbox"/>	Emulsion <input checked="" type="checkbox"/>
Piston Black				Piston White			
Drilled <input type="checkbox"/>	Hole Size 1.30 mm	 Shock Length 95.8 mm		Drilled <input type="checkbox"/>	Hole Size 1.20 mm	 Shock Length 83.15 mm	

Rear Suspension		Anti-squat Washers	
Anti roll bar No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/> Wheelbase Short <input type="checkbox"/> Med <input type="checkbox"/> Long <input checked="" type="checkbox"/> Rear Toe-in & Track Washers 0.00 Difference = 0.00° Toe-in <input type="checkbox"/> 0.50 Difference = 0.60° Toe-in <input type="checkbox"/> 1.00 Difference = 1.30° Toe-in <input type="checkbox"/> 1.50 Difference = 1.95° Toe-in <input type="checkbox"/> 2.00 Difference = 2.60° Toe-in <input type="checkbox"/> 2.50 Difference = 3.25° Toe-in <input checked="" type="checkbox"/> 3.00 Difference = 3.90° Toe-in <input type="checkbox"/> Rear 0 mm Front 0 mm		Camber at Ride Height -1.0 Deg Ride Height 21 mm 0.00 Difference = 0.00° Toe-in <input type="checkbox"/> 0.50 Difference = 0.60° Toe-in <input type="checkbox"/> 1.00 Difference = 1.30° Toe-in <input type="checkbox"/> 1.50 Difference = 1.95° Toe-in <input type="checkbox"/> 2.00 Difference = 2.60° Toe-in <input checked="" type="checkbox"/> 2.50 Difference = 3.25° Toe-in <input type="checkbox"/> 3.00 Difference = 3.90° Toe-in <input type="checkbox"/> Rear mm Front mm	
		33.5 (1 Dink) <input type="checkbox"/> 38.0 (2 Dink) <input type="checkbox"/> 42.5 (3 Dink) <input checked="" type="checkbox"/> Pin High <input checked="" type="checkbox"/> Pin Low <input type="checkbox"/>	
		Link Washers 2.0 mm	
		Rear Hub Carrier Alloy <input type="checkbox"/> Std <input checked="" type="checkbox"/> Alloy Hub Carrier +1° <input type="checkbox"/> -1° <input type="checkbox"/>	
Blocks Moulded <input checked="" type="checkbox"/> Alloy <input type="checkbox"/>			

Front Suspension		Washers 0 mm	
Anti roll bar No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/> Ride Height 20 mm Track Washers 1.0 mm Link Washers 1.0 mm Front Rake 10.0 Deg <input type="checkbox"/> 7.5 Deg <input checked="" type="checkbox"/>		Front Yoke (Kit) 12.5 <input type="checkbox"/> 10.0 <input type="checkbox"/> 7.5 <input checked="" type="checkbox"/>	
		Front Rake 10.0 Deg <input type="checkbox"/> 7.5 Deg <input checked="" type="checkbox"/>	
		Front Yoke (Kit) 12.5 <input type="checkbox"/> 10.0 <input type="checkbox"/> 7.5 <input checked="" type="checkbox"/>	
		Blocks Moulded <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>	