

Driver & Event	
Name	Tom Yardy
Date	27/9/15
Event	Summer series - Telford
Weather	Dry and warm
Result	TQ and Win

Electrics & Chassis	
E.S.C	Hobbywing
Servo	Highest
Receiver	Sanwa
Batteries	Intellect
Shorty Conversion	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Low Grip Conversion	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Chassis	Alloy <input checked="" type="checkbox"/> Carbon <input type="checkbox"/>

Motor & Gearing	
Motor	7.5
Rotor Diameter	
Timing	
Spur	76
Pinion	25

Track Conditions	
Grip Level	High <input checked="" type="checkbox"/> Med <input type="checkbox"/> Low <input type="checkbox"/>
Type	Tight <input type="checkbox"/> Open <input type="checkbox"/> Mixed <input checked="" type="checkbox"/>
Surface	Clay <input type="checkbox"/> Astro <input checked="" type="checkbox"/> Grass <input type="checkbox"/> Mixed <input type="checkbox"/> Carpet <input type="checkbox"/>
Condition	Smooth <input type="checkbox"/> Bumpy <input checked="" type="checkbox"/>

Wheels & Tyres	
Rr Tyre	Sch Yellow spike
Rr Wheel	Sch
Rr Insert	Blue
Fr Tyre	Uncut stagger LP
Fr Wheel	Sch
Fr Insert	n/a

Notes	
Car weight	g
Wing Gurney Height	o mm
Using the new Mid conversion, with battery ahead of motor... 20g under tranny case.	

Diff Type	
Ball	<input checked="" type="checkbox"/>
Gear	<input type="checkbox"/>
Diff Oil	

Front Shocks	
Oil	500cst
Spring	4.5lb
Shock Cap	Sealed <input type="checkbox"/> Vented <input type="checkbox"/>
Emulsion	<input checked="" type="checkbox"/>
Piston	3 hole
Drilled	<input type="checkbox"/>
Hole Size	1.5 mm
Shock Lengthmm

Rear Shocks	
Oil	ae 32.5
Spring	Core Red
Shock Cap	Sealed <input type="checkbox"/> Vented <input type="checkbox"/>
Emulsion	<input checked="" type="checkbox"/>
Piston	3 hole
Drilled	<input type="checkbox"/>
Hole Size	1.6 mm
Shock Lengthmm

Front Suspension	
C.T.R	Alloy <input checked="" type="checkbox"/> Kit <input type="checkbox"/>
Yoke	0° <input type="checkbox"/> 5° <input checked="" type="checkbox"/> Alloy <input type="checkbox"/>
Hub Carrier	Alloy <input checked="" type="checkbox"/> High <input type="checkbox"/> Middle <input checked="" type="checkbox"/> Low <input type="checkbox"/>
Front Wishbones Kit	<input checked="" type="checkbox"/> Reversed <input checked="" type="checkbox"/> Med Flex <input type="checkbox"/>
Link Washers	1 mm
Alloy	<input checked="" type="checkbox"/> 50.50 <input checked="" type="checkbox"/> 42.50 <input type="checkbox"/>
Front Ride Height	19 mm
Front Camber at Ride Height	1.5 Deg
Front Toe In	0 Deg

Rear Suspension	
Anti-squat	0° <input type="checkbox"/> 3° <input type="checkbox"/> 1° <input type="checkbox"/> 4° <input type="checkbox"/> 2° <input checked="" type="checkbox"/>
Wheelbase	Short <input type="checkbox"/> Med <input type="checkbox"/> Long <input checked="" type="checkbox"/>
Anti roll bar	No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>
Link Washers	mm
Alloy	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Rear Ride Height	19 mm
Rear Camber at Ride Height	1.5 Deg
Rear Toe In (Flats IN 2.5°)	<input type="checkbox"/> (Flats OUT 3.0°) <input checked="" type="checkbox"/>

