

Driver and Event	
Name	Carson Wernimont
Date	October '14
Event	EOS Rd1 - Poland
Weather	Indoors
Result	TQ & 4th

Track Conditions	
Surface	100% Carpet
Grip Level	Medium
Track Condition	Smooth, Wooden Jumps, Flat Lands



Electrics and Gearing	
E.S.C	Reedy Blackbox
Servo	Futaba
Receiver	Futaba
Batteries	Reedy Saddle
Motor	Reedy 7.5
Spur	76
Pinion	23
Side Gears	<input checked="" type="checkbox"/> 23T/33T Kit <input type="checkbox"/> 21T/35T <input type="checkbox"/> 25T/31T

Wheels and Tyres	
Rear Wheels	Schumacher Hex (U4366)
Rear Tyre	Sch Yellow MiniPin (U6608)
Rear Insert	Schumacher Medium (U6734)
Front Wheels	Schumacher Slim (U4661)
Front Tyre	Sch Yellow Stagger (U6770)
Front Insert	None

Additional Settings	
Car Weight	
Washers Between CTR and Bellcranks	4.0 mm
Bump Steer Washers	5.0 mm
Wing Gurney Height	Med Line mm

NOTES
Rear Mounted Rear Shocks (U4616), Alloy 5 Deg Front Yokes (U4228), Alloy Rear Block Conversion (U4160), TrishBits Bumper Weight & Saddle Weight, SV2 Rear Arm (U4055), KR CVA's (U4069), Rear ARB (U4172), Only 2x Internal Gears in Diff,

Diff Type	
Ball <input type="checkbox"/>	Gear <input checked="" type="checkbox"/>
Diff Oil	
10,000	

Front Shocks	
Oil	Spring
Core RC 450	Core RC Red
Shock Cap Sealed <input type="checkbox"/>	Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
Piston 3 Hole	
Drilled <input type="checkbox"/>	Hole Size Std mm
Shock Length 19.20 mm	

Rear Shocks	
Oil	Spring
Core RC 400	Core RC Blue
Shock Cap Sealed <input type="checkbox"/>	Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
Piston 3 Hole	
Drilled <input checked="" type="checkbox"/>	Hole Size 1.60 mm
Shock Length 27.70 mm	

Front Suspension	
Link Washers 1.0 mm	Yoke 0° <input type="checkbox"/> 5° <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>
Front Wishbones Kit <input checked="" type="checkbox"/> Reversed <input type="checkbox"/>	Hub Carrier High <input checked="" type="checkbox"/> Middle <input type="checkbox"/> Low <input type="checkbox"/>
Front Ride Height 19 mm	60.0 <input type="checkbox"/> 50.5 <input checked="" type="checkbox"/> 45.5 <input type="checkbox"/> 40.5 <input type="checkbox"/>
Front Camber at Ride Height -1.0 Deg	
Front Toe In +/- 0 Deg	

Rear Suspension	
Anti roll bar No <input type="checkbox"/> 1.00 <input checked="" type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>	Camber at Ride Height -1.0 Deg
Wheelbase Short <input checked="" type="checkbox"/> Med <input type="checkbox"/> Long <input type="checkbox"/>	Ride Height 19 mm
Rear Toe-in & Track Washers	Anti-squat Washers
0.00 Difference = 0.00° Toe-in <input type="checkbox"/>	0.50 Difference = 0.60° Anti-squat <input type="checkbox"/>
0.50 Difference = 0.60° Toe-in <input type="checkbox"/>	1.00 Difference = 1.30° Anti-squat <input checked="" type="checkbox"/>
1.00 Difference = 1.30° Toe-in <input type="checkbox"/>	1.50 Difference = 1.95° Anti-squat <input type="checkbox"/>
1.50 Difference = 1.95° Toe-in <input type="checkbox"/>	2.00 Difference = 2.60° Anti-squat <input type="checkbox"/>
2.00 Difference = 2.60° Toe-in <input type="checkbox"/>	2.50 Difference = 3.25° Anti-squat <input type="checkbox"/>
2.50 Difference = 3.25° Toe-in <input checked="" type="checkbox"/>	3.00 Difference = 3.90° Anti-squat <input type="checkbox"/>
3.00 Difference = 3.90° Toe-in <input type="checkbox"/>	
Rear 2.5 mm Front 0 mm	Rear 0 mm Front 3.50 mm
Blocks Moulded <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>	Link Washers 3.0 mm
Rear Hub Carrier Alloy <input type="checkbox"/> Std <input checked="" type="checkbox"/>	Pin High R <input type="checkbox"/> F <input checked="" type="checkbox"/>
Alloy Hub Carrier +1° <input type="checkbox"/> -1° <input type="checkbox"/>	Pin Low R <input checked="" type="checkbox"/> F <input type="checkbox"/>
	33.5 (1 Dink) <input type="checkbox"/>
	38.0 (2 Dink) <input type="checkbox"/>
	42.5 (3 Dink) <input checked="" type="checkbox"/>