

Driver and Event	
Name	Nathan Waters
Date	05/10/14
Event	Indoor Masters
Weather	
Result	Q2 F5

Track Conditions	
Surface	Cork Floor
Grip Level	Low
Track Condition	



Additional Settings	
Car Weight	1550
Washers Between CTR and Bellcranks	0 mm
Bump Steer Washers	0 mm
Wing Gurney Height	mm

Electrics and Gearing	
E.S.C	Dualsky
Servo	Ko
Receiver	Ko
Batteries	Dualsky Shorty
Motor	Dualsky 7.5
Spur	76
Pinion	24
Side Gears	23T/33T Kit <input type="checkbox"/> 21T/35T <input checked="" type="checkbox"/> 25T/31T <input type="checkbox"/>

Wheels and Tyres	
Rear Wheels	Schumacher Revlite
Rear Tyre	Schumacher Mini Pin
Rear Insert	Schumacher Medium
Front Wheels	Schumacher Revlite
Front Tyre	Schumacher Mini Pin Slim
Front Insert	Schumacher Medium

NOTES
 Low grip chassis (U4586) with rear mounted motor and shorty lipo
 Rear mounted rear shocks (U4616)
 SV2 rear arms not flipped (U4055)

Diff Type	Diff Oil
Ball <input checked="" type="checkbox"/>	Gear <input type="checkbox"/>

Front Shocks	
Oil	Spring
500	Blue
Shock Cap Sealed <input type="checkbox"/>	Vented <input checked="" type="checkbox"/> Emulsion <input type="checkbox"/>
	Piston 3 Hole Standard
Drilled <input type="checkbox"/>	Hole Size mm
Shock Length mm	

Rear Shocks	
Oil	Spring
400	Blue
Shock Cap Sealed <input type="checkbox"/>	Vented <input checked="" type="checkbox"/> Emulsion <input type="checkbox"/>
	Piston 1.6mm
Drilled <input type="checkbox"/>	Hole Size mm
Shock Length mm	

Front Suspension	
Link Washers 1 mm	Yoke 0° <input type="checkbox"/> 5° <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>
	Front Wishbones Kit <input type="checkbox"/> Reversed <input checked="" type="checkbox"/>
Hub Carrier High <input type="checkbox"/> Middle <input checked="" type="checkbox"/> Low <input type="checkbox"/>	60.0 <input type="checkbox"/> 50.5 <input checked="" type="checkbox"/> 45.5 <input type="checkbox"/> 40.5 <input type="checkbox"/>
Front Ride Height 19 mm	
Front Camber at Ride Height -0.5 Deg	
Front Toe In 0 Deg	

Rear Suspension	
Anti roll bar No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>	Camber at Ride Height -1.5 Deg
Wheelbase Short <input type="checkbox"/> Med <input checked="" type="checkbox"/> Long <input type="checkbox"/>	Ride Height 19 mm
Anti-squat Washers	
0.00 Difference = 0.00° Anti-squat <input type="checkbox"/>	
0.50 Difference = 0.60° Anti-squat <input type="checkbox"/>	
1.00 Difference = 1.30° Anti-squat <input type="checkbox"/>	
1.50 Difference = 1.95° Anti-squat <input type="checkbox"/>	
2.00 Difference = 2.60° Anti-squat <input type="checkbox"/>	
2.50 Difference = 3.25° Anti-squat <input type="checkbox"/>	
3.00 Difference = 3.90° Anti-squat <input type="checkbox"/>	
Rear Toe-in & Track Washers	
0.00 Difference = 0.00° Toe-in <input type="checkbox"/>	
0.50 Difference = 0.60° Toe-in <input type="checkbox"/>	
1.00 Difference = 1.30° Toe-in <input type="checkbox"/>	
1.50 Difference = 1.95° Toe-in <input type="checkbox"/>	
2.00 Difference = 2.60° Toe-in <input type="checkbox"/>	
2.50 Difference = 3.25° Toe-in <input type="checkbox"/>	
3.00 Difference = 3.90° Toe-in <input type="checkbox"/>	
Rear 0 mm Front 0 mm	
	33.5 (1 Dink) <input type="checkbox"/>
	38.0 (2 Dink) <input checked="" type="checkbox"/>
	42.5 (3 Dink) <input type="checkbox"/>
Pin High R <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/>	
Pin Low R <input type="checkbox"/> F <input type="checkbox"/>	
Rear Hub Carrier Alloy <input type="checkbox"/> Std <input checked="" type="checkbox"/>	
Alloy Hub Carrier +1° <input type="checkbox"/> -1° <input type="checkbox"/>	
Link Washers 3 mm	
Blocks Moulded <input checked="" type="checkbox"/> Alloy <input type="checkbox"/>	