

Driver and Event	
Name	Tom Cockerill
Date	September '13
Event	IFMAR Worlds
Weather	Warm
Result	22nd

Track Conditions	
Surface	Sugared Clay
Grip Level	High
Track Condition	Smooth, Jumps



Additional Settings	
Car Weight	1735g
Washers Between CTR and Bellcranks	4.0 mm
Bump Steer Washers	4.0 mm
Wing Gurney Height	Med Line mm

Wheels and Tyres	
Rear Wheels	Schumacher
Rear Tyre	Handout
Rear Insert	Handout
Front Wheels	Schumacher
Front Tyre	Handout
Front Insert	N/A

Diff Type	
Ball <input type="checkbox"/>	Gear <input checked="" type="checkbox"/>
Diff Oil	
Core RC 7,000	

NOTES  
KR CVA Drive Shafts

Electrics and Gearing	
E.S.C	Nosram Comet HD
Servo	Sanwa
Receiver	KO
Batteries	Nosram 5800 Saddle
Motor	Nosram Pure 2 7.5
Spur	76
Pinion	23
Side Gears	23T/33T Kit <input checked="" type="checkbox"/>
	21T/35T <input type="checkbox"/>
	25T/31T <input type="checkbox"/>

Front Shocks	
Oil	Spring
CoreRC 500	CoreRC Black
Shock Cap Sealed <input type="checkbox"/>	Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
Piston	3 x 1.55 (Kit)
Drilled <input type="checkbox"/>	Hole Size Std mm
Shock Length 83.3 mm	

Rear Shocks	
Oil	Spring
CoreRC 450	CoreRC Black
Shock Cap Sealed <input type="checkbox"/>	Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
Piston	3 Hole
Drilled <input checked="" type="checkbox"/>	Hole Size 1.65 mm
Shock Length 95.4 mm	

Front Suspension	
Link Washers 1.0 mm	Yoke 0° <input checked="" type="checkbox"/> 5° <input type="checkbox"/> Alloy <input type="checkbox"/>
Front Wishbones Kit <input type="checkbox"/> Reversed <input checked="" type="checkbox"/>	Hub Carrier High <input checked="" type="checkbox"/> Middle <input type="checkbox"/> Low <input type="checkbox"/>
Front Ride Height 20 mm	60.0 <input type="checkbox"/> 50.5 <input checked="" type="checkbox"/> 45.5 <input type="checkbox"/> 40.5 <input type="checkbox"/>
Front Camber at Ride Height -1.0 Deg	
Front Toe In -1.0 Deg	

Rear Suspension	
Anti roll bar No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>	Camber at Ride Height -1.0 Deg
Wheelbase Short <input checked="" type="checkbox"/> Med <input type="checkbox"/> Long <input type="checkbox"/>	Ride Height 20 mm
Rear Toe-in & Track Washers	Anti-squat Washers
0.00 Difference = 0.00° Toe-in <input type="checkbox"/>	0.00 Difference = 0.00° Anti-squat <input type="checkbox"/>
0.50 Difference = 0.60° Toe-in <input type="checkbox"/>	0.50 Difference = 0.60° Anti-squat <input type="checkbox"/>
1.00 Difference = 1.30° Toe-in <input type="checkbox"/>	1.00 Difference = 1.30° Anti-squat <input type="checkbox"/>
1.50 Difference = 1.95° Toe-in <input type="checkbox"/>	1.50 Difference = 1.95° Anti-squat <input type="checkbox"/>
2.00 Difference = 2.60° Toe-in <input type="checkbox"/>	2.00 Difference = 2.60° Anti-squat <input checked="" type="checkbox"/>
2.50 Difference = 3.25° Toe-in <input checked="" type="checkbox"/>	2.50 Difference = 3.25° Anti-squat <input type="checkbox"/>
3.00 Difference = 3.90° Toe-in <input type="checkbox"/>	3.00 Difference = 3.90° Anti-squat <input type="checkbox"/>
Rear 2.5 mm Front 0 mm	Rear 0 mm Front 3.0 mm
Blocks Moulded <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>	Link Washers 3.0 mm
Rear Hub Carrier Alloy <input type="checkbox"/> Std <input checked="" type="checkbox"/>	33.5 (1 Dink) <input type="checkbox"/>
Alloy Hub Carrier +1° <input type="checkbox"/> -1° <input type="checkbox"/>	38.0 (2 Dink) <input type="checkbox"/>
	42.5 (3 Dink) <input checked="" type="checkbox"/>
	Pin High R <input type="checkbox"/> F <input checked="" type="checkbox"/>
	Pin Low R <input checked="" type="checkbox"/> F <input type="checkbox"/>