

Driver and Event	
Name	TOM COCKERILL
Date	OCT 2013
Event	E.O.S RD 1
Weather	INDOOR
Result	TQ + 5TH

Track Conditions	
Surface	CARPET
Grip Level	MEDIUM
Track Condition	TIGHT, TECHNICAL



Additional Settings	
Car Weight	1710g
Washers Between CTR and Bellcranks	4.0 mm
Bump Steer Washers	4.0 mm
Wing Gurney Height	5.0 mm

Electrics and Gearing	
E.S.C	NOSRAM COMET HD
Servo	SANWA
Receiver	KO
Batteries	NOSRAM 5800
Motor	NOSRAM PURE 2 7.5
Spur	76T
Pinion	23T
Side Gears	23T/33T Kit <input checked="" type="checkbox"/> 21T/35T <input type="checkbox"/> 25T/31T <input type="checkbox"/>

Wheels and Tyres	
Rear Wheels	SCHUMACHER
Rear Tyre	HANDOUT
Rear Insert	HANDOUT
Front Wheels	SCHUMACHER
Front Tyre	HANDOUT
Front Insert	NIA

NOTES
CORE RC OILS AND SPRINGS
SADDLE PACK CELLS
KR DRIVESHAFTS

Diff Type	
Ball <input type="checkbox"/> Gear <input checked="" type="checkbox"/>	Diff Oil 10,000

Front Shocks	
Oil 450	Shock Cap Sealed <input type="checkbox"/>
Spring GREEN	Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
	Piston 3 HOLE
Drilled <input type="checkbox"/>	Hole Size STD mm
Shock Length 81.8 mm	

Rear Shocks	
Oil 450	Shock Cap Sealed <input type="checkbox"/>
Spring BLACK	Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
	Piston 3 HOLE
Drilled <input checked="" type="checkbox"/>	Hole Size 1.65 mm
Shock Length 95.4 mm	

Front Suspension	
Link Washers 1.0 mm	Yoke 0° <input checked="" type="checkbox"/> 5° <input type="checkbox"/> Alloy <input type="checkbox"/>
Front Ride Height 18.0 mm	Front Wishbones Kit <input type="checkbox"/> Reversed <input checked="" type="checkbox"/>
Front Camber at Ride Height -1.0 Deg	Hub Carrier High <input type="checkbox"/> Middle <input type="checkbox"/> Low <input checked="" type="checkbox"/>
Front Toe In -1.0 Deg	60.0 <input type="checkbox"/> 50.5 <input checked="" type="checkbox"/> 45.5 <input type="checkbox"/> 40.5 <input type="checkbox"/>

Rear Suspension	
Anti roll bar No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>	Camber at Ride Height -1.5 Deg
Wheelbase Short <input checked="" type="checkbox"/> Med <input type="checkbox"/> Long <input type="checkbox"/>	Ride Height 18 mm
Rear Toe-in & Track Washers	Anti-squat Washers
0.00 Difference = 0.00° Toe-in <input type="checkbox"/>	0.50 Difference = 0.60° Toe-in <input type="checkbox"/>
0.50 Difference = 0.60° Toe-in <input type="checkbox"/>	1.00 Difference = 1.30° Toe-in <input type="checkbox"/>
1.00 Difference = 1.30° Toe-in <input type="checkbox"/>	1.50 Difference = 1.95° Toe-in <input type="checkbox"/>
1.50 Difference = 1.95° Toe-in <input type="checkbox"/>	2.00 Difference = 2.60° Toe-in <input checked="" type="checkbox"/>
2.00 Difference = 2.60° Toe-in <input type="checkbox"/>	2.50 Difference = 3.25° Toe-in <input type="checkbox"/>
2.50 Difference = 3.25° Toe-in <input checked="" type="checkbox"/>	3.00 Difference = 3.90° Toe-in <input type="checkbox"/>
3.00 Difference = 3.90° Toe-in <input type="checkbox"/>	Rear 0 mm Front 3.0 mm
Rear 2.5 mm Front 0 mm	33.5 (1 Dink) <input type="checkbox"/>
	38.0 (2 Dink) <input type="checkbox"/>
	42.5 (3 Dink) <input checked="" type="checkbox"/>
	Rear Hub Carrier Alloy <input type="checkbox"/> Std <input checked="" type="checkbox"/>
	Alloy Hub Carrier +1° <input type="checkbox"/> -1° <input type="checkbox"/>
Blocks Moulded <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>	Link Washers 3.0 mm