

Driver and Event

Name
Date
Event
Weather
Result

Track Conditions

Surface
Grip Level
Track Condition

COUGAR^{KR}

Additional Settings

Car Weight
Washers between
CTR and Bellcranks mm
Chassis Alloy ☐ Carbon ☐

NOTES

Electrics and Gearing

E.S.C
Servo
Receiver
Batteries
Motor
Spur
Pinion
Cell Position

Wheels and Tyres

Rear Wheels
Rear Tyre
Rear Insert
Front Wheels
Front Tyre
Front Insert

Diff Type
Ball ☐ Gear ☐ Diff Oil

Front Shocks

Oil Spring Shock Cap Sealed ☐
Vented ☐ Emulsion ☐
Piston
Drilled ☐ Hole Size mm Shock Length mm

Rear Shocks

Oil Spring Shock Cap Sealed ☐
Vented ☐ Emulsion ☐
Piston
Drilled ☐ Hole Size mm Shock Length mm

Front Suspension

Link Washers mm

Yoke 0° ☐ 5° ☐ Alloy ☐

Hub Carrier
High ☐ Middle ☐ Low ☐

Front Ride Height mm
Front Camber at Ride Height Deg
Front Toe In Deg

60.0 ☐ 50.5 ☐ 45.5 ☐ 40.5 ☐

Rear Suspension

Anti roll bar No ☐ 1.20 ☐ 1.40 ☐ 1.60 ☐

Toe-In 2° ☐ 3° ☐

Link Washers mm

AntiSquat 3° ☐ 2° ☐ 1° ☐ 0° ☐

Wheelbase Short ☐ Med ☐ Long ☐

Rear Ride Height mm
Rear Camber at Ride Height Deg

Rear Hub Carrier Alloy ☐ Std ☐
Alloy Hub Carrier +1° ☐ -1° ☐

49 ☐ 44 ☐ 39 ☐ 34 ☐