

Driver and Event	
Name	<b>TOM COCKERILL</b>
Date	<b>JUNE 2013</b>
Event	<b>TEST</b>
Weather	<b>DRY - HOT</b>
Result	<b>NIA</b>

Track Conditions	
Surface	<b>CLAY</b>
Grip Level	<b>MEDIUM - HIGH</b>
Track Condition	<b>BLUE GROOVE</b>



Additional Settings	
Car Weight	<b>1735g</b>
Washers between CTR and Bellcranks	<b>4.0 mm</b>
Chassis Alloy	<input type="checkbox"/>
Carbon	<input checked="" type="checkbox"/>

Electrics and Gearing	
E.S.C	<b>NOSRAM COMET</b>
Servo	<b>ANDERSON</b>
Receiver	<b>KO</b>
Batteries	<b>NOSRAM 5800</b>
Motor	<b>NOSRAM 8.5</b>
Spur	<b>76T</b>
Pinion	<b>24T</b>
Cell Position	<b>20mm FROM FULLY BACK</b>

Wheels and Tyres	
Rear Wheels	<b>SCHUMACHER</b>
Rear Tyre	<b>PL HOLESHOT</b>
Rear Insert	<b>CLOSED CELL</b>
Front Wheels	<b>SCHUMACHER</b>
Front Tyre	<b>PROLINE RIB</b>
Front Insert	<b>STD</b>

Diff Type	
Ball	<input checked="" type="checkbox"/>
Gear	<input type="checkbox"/>
Diff Oil	

NOTES

**40g AROUND SERVO**

Front Shocks	
Oil	<b>CORE 450</b>
Spring	<b>CORE GREEN</b>
Shock Cap Sealed	<input type="checkbox"/>
Vented	<input type="checkbox"/>
Emulsion	<input checked="" type="checkbox"/>
Piston	<b>3 HOLE</b>
Drilled	<input type="checkbox"/>
Hole Size	<b>STD mm</b>
Shock Length	<b>83 mm</b>

Rear Shocks	
Oil	<b>CORE 350</b>
Spring	<b>CORE RED</b>
Shock Cap Sealed	<input type="checkbox"/>
Vented	<input type="checkbox"/>
Emulsion	<input checked="" type="checkbox"/>
Piston	<b>3 HOLE</b>
Drilled	<input type="checkbox"/>
Hole Size	<b>STD mm</b>
Shock Length	<b>97 mm</b>

Front Suspension	
Link Washers	<b>1.0 mm</b>
Yoke	0° <input type="checkbox"/> 5° <input checked="" type="checkbox"/> Alloy <input type="checkbox"/>
Hub Carrier	High <input type="checkbox"/> Middle <input checked="" type="checkbox"/> Low <input type="checkbox"/>
Front Ride Height	<b>24.0 mm</b>
Front Camber at Ride Height	<b>-2.0 Deg</b>
Front Toe In	<b>0.0 Deg</b>
Wheelbase	60.0 <input type="checkbox"/> 50.5 <input checked="" type="checkbox"/> 45.5 <input type="checkbox"/> 40.5 <input type="checkbox"/>

Rear Suspension	
Anti roll bar	No <input checked="" type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>
Toe-In	2° <input type="checkbox"/> 3° <input checked="" type="checkbox"/>
Link Washers	<b>2.0 mm</b>
AntiSquat	3° <input type="checkbox"/> 2° <input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0° <input type="checkbox"/>
Wheelbase	Short <input type="checkbox"/> Med <input checked="" type="checkbox"/> Long <input type="checkbox"/>
Rear Ride Height	<b>24.0 mm</b>
Rear Camber at Ride Height	<b>-2.0 Deg</b>
Rear Hub Carrier	Alloy <input type="checkbox"/> Std <input checked="" type="checkbox"/>
Alloy Hub Carrier	+1° <input type="checkbox"/> -1° <input type="checkbox"/>
Wheelbase	49 <input type="checkbox"/> 44 <input type="checkbox"/> 39 <input type="checkbox"/> 34 <input checked="" type="checkbox"/>