SETUP SHEET SPUDER





DRIVER, TRACK AND RESULTS	
DRIVER Marius Kristensen COUNTRY Slovakia WEA	THER AIR TEMP to hot TRACK TEMP to hot DRY INTERMEDIATE WET
RACE EOS RD3 DATE QUA	LY POS. STARTING POS. FINAL POS. FASTEST LAP
TRACK hudy arena TYPE ✓ INDOOR □ OUTDOOR STYLE □ TIGHT □ MEDIUM □ OPEN □	
SURFACE GRIP LOW MEDIUM HIGH CONDITION SMOOTH ROUGH TYPE HARD PACKED CLAY CARPET MULTI/SURFACE GRASS BLUE GROOVE DIRT ASTRO-TURF	
FRONT SHOCK ABSORBERS REAR 1000 cst OIL 450 cst	FRONT REAR SHOCK LEFT REAR UPRIGHT RIGHT
1000 cst OIL 450 cst 4 dot SPRINGS xray 3 dot	WHEEL HEX 2wd srx2 mm SHIMS 1 mm POSITION 123 STD 1A STD 1B 1B 1B
Omm REBOUND Omm	SPINDLE
3mm LIMITERS 1mm	SHIMS UP CAMBERLINK OR CAMBERLINK OR OR OR OR OR OR OR OR OR O
N° HOLES 2 Ø 1,7 mm PISTONS N° HOLES 2 Ø 1.6 mm	
PISTONS TYPE ☐ STOCK ☐ CONICAL ✓ SQUARE	DOWN CAMBERLINK POSITION POSITION REAR ARMS LEFT RIGHT
SHORT LONG SPRING BUCKETS SHORT LONG	POSITION REAR ARMS LEFT RIGHT POSITION A B B A B
□BLADDER SEAL □BLADDER	+
	FRONT
FRONT ANTI-ROLL BARS FEAR	CAMBER R 2 °
1.0 1.2 1.4 1.6 1.8 1.0 1.2 1.4 1.6 1.8	
TRANSMISSION	RIDE HEIGHT 15 mm RIDE HEIGHT 15 mm CASTER BLOCK SHOCKS POSITION ROLL CENTER
FRONT DIFF CENTER DIFF	0° 2° ✓ 5° ✓ FRONT SPACER
cst cst cst	SHIMS 1 mm REAR YES
GEARING	
PINION 86 Teeth SPUR GEAR 20 Teeth	
ELECTRONICS	FRONT SUSPENSION BRACKETS
BATTERY	FRONT REAR STD PLUS 2 STD PLUS 2 3° 6 1° 6 9
BRAND arrowmax CAPACITY 5000mAh	ELECTRONICS LAYOUTS
MOTOR	LAYOUT 1 LAYOUT 2 LAYOUT 3 LAYOUT 4
BRAND Reedy TYPE 6.5 TIMING 30	
BRAND reedy TYPE blackbox	
AERODYNAMIC CONFIGURATION	
BODY BRAND TYPE	
REAR WING BRAND TYPE	
REAR WING WIDTH REAR WING LIP mm	
FRONT WING VES NO TYPE Jconcepts wide	
FRONT TIRES Controlled Tire REAR	FRONT TOE 0 0 WEIGHT DISTRIBUTION REAR TOE 33 0
schumacher MAKE schumacher	+ WEIGHT FR % RR %
2wd cut stagger LP TYPE mini pin 1	BIAS THE SKIN REAR ARM SKIN
yellow COMPOUND yellow	NYLON CARBON NYLON CARBON
blue INSERTS blue	CHASSIS FLEX
ADDITIVE SCHUMACHER	
ADDITIVE	

glued inserts to the arm to get them stiffer. front diff in and added 10 grams low profile servo. SDX4-2WD!!