



# SET UP

## DIFFERENTIAL OIL

FRONT	CENTER	REAR
5k CST	5k CST	4k CST

## CLUTCH

TYPE: STANDARD ☐ OPTIONAL ☐

SHOE: ALU ☐ PCS ☐ SPRING ☐

CARBON ☐ PCS ☐ SPRING ☐

## GEARING

CLUTCH BELL 16 T SPUR GEAR Stk T

## BRAKE BALANCERS

50/50	<input type="checkbox"/>	BALANCER CLIPS:	0.5 MM	pcs
OPTION	<input type="checkbox"/>		0.75MM	pcs
			1.0 MM	pcs
			1.25MM	pcs
			1.5 MM	pcs

## SHOCKS

FRONT	SPRING	REAR
C= 4.8 <input type="checkbox"/>	PINK	C= 2.8 <input type="checkbox"/>
C= 5.0 <input type="checkbox"/>	BLUE	C= 3.0 <input type="checkbox"/>
C= 5.2 <input checked="" type="checkbox"/>	PURPLE	C= 3.2 <input type="checkbox"/>
C= 5.4 <input type="checkbox"/>	GREEN	C= 3.4 <input type="checkbox"/>
C= 5.6 <input type="checkbox"/>	GREY	C= 3.6 <input type="checkbox"/>
C= 5.8 <input type="checkbox"/>	YELLOW	C= 3.8 <input checked="" type="checkbox"/>
C= 6.0 <input type="checkbox"/>	WHITE	C= 4.0 <input type="checkbox"/>
C= <input type="checkbox"/>	OTHER	C= <input type="checkbox"/>
40	OIL/CST	25
50%	REBOUND %	50%

## PISTON

### HOLES SIZE

☐ 1.1MM ☒ 1.2MM ☐ 1.3MM ☐ 1.4 MM

8-Hole Flat OTHER 8-Hole Flat

## TYRES

## BODY

BRAND	BRAND	Stock
TYPE	TYPE	
INSERT	WING	OPTIONAL
WHEELS	STOCK	BRAND
	TYPE	

## ENGINE

TYPE

MANIFOLD

MUFFLER

PLUG

FUEL

## COMMENTS

16T Pinion  
Tekin RX8 / 1900Kv Combo  
5300mah 50C Lipo's

NAME	Cobra -Be	RACE	Indy RC World	DATE	
TRACK		CITY/COUNTRY	Garland, TX	CONTACT	
TRACK SIZE	<input type="checkbox"/> OPEN <input checked="" type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> TIGHT	TEMP. F° / °C			
TRACK TRACTION	<input type="checkbox"/> HIGH <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> LOW	AIR		TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> SMOOTH <input type="checkbox"/> MEDIUM <input type="checkbox"/> BUMPY	LAPS			
TRACK TYPE	<input checked="" type="checkbox"/> HARD PACKED <input type="checkbox"/> SOFT DIRT <input type="checkbox"/> CLAY	BEST LAPTIME		in LAP	
	<input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> ASTRO TURF <input type="checkbox"/> GRASS	RACE LENGTH			
TRACK CONDITION	<input type="checkbox"/> DRY <input type="checkbox"/> DUSTY <input type="checkbox"/> MUD	RACE RESULT			

STEERING BLOCK ☒ PLASTIC ☐ ALU

CASTER BLOCK ☒ PLASTIC ☐ ALU

UPRIGHT ☒ PLASTIC ☐ ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

CASTER ☒ 10° ☐ 12°

SPINDLE ☐ HIGH ☒ LOW

BRACE ☒ PLASTIC ☐ ALU

INSERT NR. 4 ☒ UP ☐ DOWN

INSERT NR. 5 ☒ IN ☐ OUT

BRACE ☒ PLASTIC ☐ ALU

STANDARD BRACKET ☒ STANDARD BRACKET ☐ OPTIONAL TYPE

OPTIONAL TYPE

ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☐ 2.3MM ☒ 2.5MM ☐ 2.7MM

OUT (-) ☐ 0° ☐ +°

FRONT TOE

SERVO SAVER SPRING ☐ STANDARD ☒ HARD

STEERING BAR ☐ OPT 1 ☒ OPT 2 ☐ OPT 3

WHEELBASE SHIMS ☒ 1.25 ☐ 2.5 ☐ 3.75 ☐ 5MM

WING LOCATION IN MM Stk

ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☐ 2.3MM ☒ 2.5MM ☐ 2.7MM

FRONT CAMBER ☐ +° ☒ -2° ☐ +°

SHOCKLENGTH AT FULL DROOP 99 MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 26 MM

REAR CAMBER ☐ -2° ☒ +°

SHOCKLENGTH AT FULL DROOP 114 MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 27 MM