


FRONT SUSPENSIONS




Diameter of A.R.B : mm
Bumpsteer Washers : 0
Camber angle : -15
Toe angle : 0
Ride Height : 22 mm

Steering rack:




Camber Links:



Washers : 0


Shock Position:



A Arm: 0 I



REAR SUSPENSIONS



Diameter of A.R.B : 10mm
Hub Tower : A B
Camber angle : -15
Toe angle : +1.0 (total +4.0)
Ride Height : 23 mm
Wheelbase : Long / Med / Short

A Arm:




Camber Links:



Washers : 2mm

Shock Position:



FRONT SHOCKS

Spring: AV D Red **Piston:** #2
Shock oil: AE #40 **Limiter:** 10mm

REAR SHOCKS

Spring: AV D Yellow **Piston:** #1
Shock oil: AE #35 **Limiter:** 25mm

Shocks: AE / AE 12mm / Losi / Kyosho / Tamiya / Durango / Other

DIFFERENTIALS

Front Diff setting: Tight
Rear Diff setting: Lose

AERO DEVICE

Body: Grayseal **Rear Wing:** AZ-0034 N-Splend
Wing Angle : **Front Wing:**

FRONT TIRES

Tire / Compound: Panther T725C
Insert: P/L C bsd Cell **Wheel:** AE

REAR TIRES

Tire / Compound: Panther T755C
Insert: P/L C bsd Cell **Wheel:** AE

ELECTRONICS

Motor: Dry Hop BL 75T **ESC:** S/P 20GT
Pinion / Spur : 27 / 81T **Servo:** SANWA SRG-BLS

Radio: SANWA **Receiver:** RX451R
ESC Setting:

TRACK INFO

Traction: High / Medium / Low **Surface:** Smooth / Bumpy **SoftDirt / Grass / Clay / Astroturf** **Dry / Wet** **Dusty / Clean**

- Use AV D AV1020-MOD TRAD Slipper. •Use AV D AV1014 and AV1012 •Rear wingmount B-MAX4(BM-001) use
- Weights psitions 35g at the center of the rear side. 15g at the center of the front side.
- Totalweight 1645g